

# PRODUCT DATASHEET

## ST CLAS A 150 19 W/2700K E27

LED STAR CLASSIC A | LED lamps, classic bulb shape



---

### AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

---

### PRODUCT FEATURES

- LED alternative to conventional lamps
- Mercury-free lamps



**TECHNICAL DATA**

Electrical data

Rated wattage	19.00 W
Nominal wattage	19.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	29
Max. lamp no. on circuit break. 16 A (B)	48
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.50
Claimed equiv. conventional lamp power	150 W


Photometrical data

Rated luminous flux	2451 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	2451 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdcM
Nominal luminous flux	2451 lm
Rated color temperature	2700 K
Color rendering index Ra	$\geq 80$

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	128.0 mm
----------------	----------

<b>Diameter</b>	68.0 mm
<b>Outer bulb</b>	A68
<b>Length</b>	128.0 mm

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-15...+40 °C
<b>Maximum temperature at tc test point</b>	100 °C

#### Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000
<b>Lumen maintenance at end of service life</b>	0.70

#### Additional product data

<b>Base (standard designation)</b>	E27
<b>Mercury-free</b>	Yes
<b>Design / version</b>	Frosted
<b>Show WEEE picto</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
<b>Mercury content</b>	0.0 mg

#### Capabilities

<b>Dimmable</b>	No
-----------------	----



#### Certificates & standards

<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	19 kWh/1000h

#### Country-specific categorizations

<b>ILCOS</b>	DRAA/F-20/827-220-240-E27-60
<b>Order reference</b>	LEDSCLA150 19W/

Light Distribution



LDC typ polar

LDC typ polar

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899959118	Blister 1	72 mm x 140 mm x 185 mm	190.00 g	1.86 dm <sup>3</sup>
4052899959569	Shipping carton box 6	432 mm x 153 mm x 201 mm	1351.00 g	13.29 dm <sup>3</sup>
4058075245976	Folding carton box 1	71 mm x 71 mm x 135 mm	176.00 g	0.68 dm <sup>3</sup>
4058075245983	Shipping carton box 10	372 mm x 153 mm x 144 mm	1902.00 g	8.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For further products and actual information concerning LED lamps see

- ▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.