



Environmentally preferable to traditional technologies, these Non-Cutoff Wall Packs offer dual selectability and an optional sensor for further energy savings. The UV stabilized polycarbonate lens, IK08 rating, and 10-year warranty ensure a long lasting and robust luminaire perfect for lighting outdoor corridors, walkways, and stairwells.

SUPERIOR CLASS



For more information, visit www.ledvanceUS.com/luminaires



LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone 1-800-LIGHTBULB
(1-800-544-4828)

SUPERIOR CLASS NON-CUTOFF WALL PACK 6A

Item Number	Ordering Abbreviation	Wattage (W)	Input Voltage (V)	Dimming	CRI	Color Temperature (CCT)	Distribution	Total Fixture Lumens	LPW	MTO*
62727	WALPAKN6AS040UNVD8SC2T2BZP	15/25/40	120-277V	0-10V	>80	3000K/4000K/5000K	Type II	1950/3500/5600	Up to 140	MTO
62730	WALPAKN6AS040UNVD8SC2T4BZP	15/25/40	120-277V	0-10V	>80	3000K/4000K/5000K	Type IV	1950/3500/5600	Up to 140	-
62728	WALPAKN6AS080UNVD8SC2T2BZP	45/65/80	120-277V	0-10V	>80	3000K/4000K/5000K	Type II	6300/9100/11,200	Up to 140	MTO
62731	WALPAKN6AS080UNVD8SC2T4BZP	45/65/80	120-277V	0-10V	>80	3000K/4000K/5000K	Type IV	6300/9100/11,200	Up to 140	-
62729	WALPAKN6AS120UNVD8SC2T2BZP	75/95/120	120-277V	0-10V	>80	3000K/4000K/5000K	Type II	10,500/13,300/16,800	Up to 140	MTO
62732	WALPAKN6AS120UNVD8SC2T4BZP	75/95/120	120-277V	0-10V	>80	3000K/4000K/5000K	Type IV	10,500/13,300/16,800	Up to 140	-

*Made To Order

CONTRACTOR BENEFITS

- Standard backbox form factor to easily replace traditional luminaires
- Dual selectability for limited SKU quantity and flexibility on the job site
- Easily installed on junction boxes or as side conduit mount

SIZE

Luminaire Description	Length (inches)	Width (inches)	Height (inches)	Weight (lbs)
40W	11.3	6.9	8.6	8
80W/120W	14.4	7.6	9.3	11/11.6

BENEFITS AND FEATURES

- DLC 5.1 Premium listing and CCT and lumen selectability provide high energy efficacy and optimize this product for utility rebates
- Traditional sizes allow seamless replacement of existing luminaires
- LEDVANCE LINK™ compatibility allows for customizable light via Bluetooth Mesh
- Up to 140 LPW
- 3000K, 4000K and 5000K selectable color temperature
- CRI >80
- Wattage selectable offered in 15/25/40W, 45/65/80W, and 75/95/120W
- Non-Cutoff Type II and Type IV Distributions are available
- Energy savings up to 76%



SCAN TO FOLLOW US
ON SOCIAL MEDIA

LEDVANCE is a registered trademark. All other trademarks are those of their respective owners. Specifications subject to change without notice.

Scan the QR tag to view
or download additional
product information

