

LEDVANCE.COM

MULTI COLOUR
MULTI LUMEN
ONE SOLUTION

LEDVANCE



MULTI SELECT
YOUR BUSINESS
MADE EASY

ALWAYS THE RIGHT PRODUCT


THE MULTI SELECT LUMINAIRES


The perfect luminaire adapts to its environment. The ultra-long-life LED luminaires from the LEDVANCE MULTI SELECT range allow you to easily set the luminous flux (lm) and/or light colour on the driver or luminaire by hand. The variety of luminaire types stands for maximum flexibility, reduced stock levels and optimal lighting at all times, all with a five-year product guarantee. For more success in your daily business. Visit ledvance.com/multiselect for more information.

SELECT THE LUMINOUS FLUX AND/OR THE ...




... COLOUR TEMPERATURE ON THE LUMINAIRE







MULTI LUMEN
SPECIAL FEATURES

- LED luminaires with variable luminous flux (lumen)
- Easy-to-set luminous flux via switch on the driver or luminaire before installation
- Practical solution for optimal illumination, e.g. for different ceiling heights





MULTI COLOUR
SPECIAL FEATURES

- LED luminaires with up to three different colour temperatures (warm white, cold white, daylight white)
- Easy-to-set light colour via switch on the driver or luminaire on-site
- Adjust the light colour to specific requirements before installation

Example of products shown in this sales flyer:


84 functionalities that would require **84** different luminaires **»»** fit into only **28 luminaires**

At the flick of a switch – make the right choice
CHOOSE LEDVANCE!



BENEFITS FOR WHOLESALERS

- Leaner ranges with lower storage capacities
- Less time and effort for consultation



BENEFITS FOR INSTALLERS

- Always the right product choice
- Quick and practical solutions
- Flexible changes before or after installation

EFFICIENT AND VERSATILE SURFACE SQUARE AND CIRCULAR

- Highly versatile with multi colour (3 000/4 000/5 000 K) or multi lumen (3 500/2 500/1 500 lm), selectable on the luminaire
- Wall and ceiling luminaires
- Easy and quick installation



All product details

Product name	GTIN (EAN)	Replacement for	lm	W	lm/W	K	L70 ¹	△	L × W × H [mm] ∅ × H [mm]	Light No.
SURFACE SQUARE AND CIRCULAR										
SURFACE SQUARE 330 3CCT 24W 3CCT IP44	4099854042034	1 × 26 W CFLP	2000	24	83	3000/4000/5000	50000	120	330 × 330 × 75	1
SURFACE CIRCULAR 350 3CCT 18W 3CCT IP44	4099854042072	1 × 26 W CFLP	1440	18	80	3000/4000/5000	50000	120	350 × 75	2
SURFACE CIRCULAR 500 PS 42W 830 IP44 PS	4099854042119	2 × 32 W CFLP	3500/2500/1500	42/30/19	83/78	3000	50000	120	500 × 105	3
SURFACE CIRCULAR 500 PS 42W 840 IP44 PS	4099854042133	2 × 32 W CFLP	3500/2500/1500	42/30/19	83/78	4000	50000	120	500 × 105	3

FLEXIBLE ALL-ROUND SPOT COMBO

- Colour temperature adjustment with multi colour (2 700/3 000/4 000 K), selectable on the spot
- Brightness adjustment with two lumen packages via switch on the driver
- Additional cover rings separately available in different colours



All product details

Product name	GTIN (EAN)	Replacement for	lm	W	lm/W	K	L70 ¹	△	L × W × H [mm] ∅ × H [mm]	Light No.	
SPOT COMBO											
SPOT COMBO FIX V 5.5W CPS 60DEG IP65 WT	4099854092701	40 W INCAND.	400/600	3.5/5.5	114/109	2700/3000/4000	50000	60	68	81.5 × 48	1
SPOT COMBO ADJUST V 5.5W CPS 60DEG IP65 WT	4099854092725	40 W INCAND.	400/600	3.5/5.5	114/109	2700/3000/4000	50000	60	68	81.5 × 48	2

PRACTICAL IN ANY ENVIRONMENT DAMP PROOF COMPACT GEN 2

- Highly versatile due to multi lumen function that allows two different lumen packages
- Easy installation as mounting brackets can be positioned freely on the luminaire
- Easy access to electrical terminal thanks to end caps with twist and lock mechanism



All product details

Product name	GTIN (EAN)	Replacement for	lm	W	lm/W	K	L70 ¹	△	L × W × H [mm] ∅ × H [mm]	Light No.
DAMP PROOF COMPACT GEN 2										
DAMP PROOF COMPACT GEN 2 1200 V 33W 840 IP66 PS	4058075740877	2 × 36 W FL	3960/2600	33/21	123/120	4000	75000	120	✓	1243 × 60 × 53
DAMP PROOF COMPACT GEN 2 1500 V 50W 840 IP66 PS	4058075740891	2 × 58 W FL	6100/4200	50/34	123/122	4000	75000	120	✓	1543 × 60 × 53

¹ t[h]: L70/B50 @ 25 °C (T_a)/t[h]; L80/B10 @ 25 °C (T_a) | ² Refer to www.ledvance.com/guarantee for precise conditions

ABOUT LEDVANCE

With business activities in over 140 countries, LEDVANCE is one of the world's leading general lighting companies. Emerging from OSRAM's general lighting division, LEDVANCE's portfolio includes LED lamps and luminaires, intelligent lighting products, traditional lamps and renewable energy solutions.
#POWERTHROUGHLIGHT

LEDVANCE GmbH
Parkring 1-5
85748 Garching
Germany

LEDVANCE

FUNCTIONAL CONVENIENCE PANEL COMFORT + COMPACT

- Highly versatile due to selectable lumen packages on the driver and/or two multi colour versions with 3 000/4 000 K
- Through-wiring possible with included connector box
- External driver for extended flexibility and easy installation



Product name	GTIN (EAN)	Replacement for	lm	W	lm/W	K	L80 ¹	°	°	L x W x H [mm] Ø x H [mm]	Light No.
PANEL COMFORT CR190											
PANEL COMFORT 600 UGR<19 PS CR190 36W 930 940	4058075694460	4 x 18 W FL	4200/4000/3600/3400	36/29.5	122/118/115/112	3000/4000	60000	90	—	595 x 595 x 35	1
PANEL COMFORT CR190 DALI											
PANEL COMFORT 600 UGR<19 DALI CS CR190 36W 930 940	4058075694507	4 x 18 W FL	4200	36	118	3000/4000	60000	90	DALI-2/LoT	595 x 595 x 35	1
PANEL COMFORT UGR19											
PANEL COMFORT 600 UGR<19 PS 28W 830 U19 PS	4099854014604	4 x 18 W FL	3640/3250/2900	28/25/22	130	3000	70000	90	—	595 x 595 x 32	1
PANEL COMFORT 600 UGR<19 PS 28W 840 U19 PS	4099854014628	4 x 18 W FL	3640/3250/2900	28/25/22	130	4000	70000	90	—	595 x 595 x 32	1
PANEL COMFORT 600 UGR<19 PS 33W 830 U19 PS	4099854015090	4 x 18 W FL	4320/3900/3640	33/30/28	130	3000	70000	90	—	595 x 595 x 32	1
PANEL COMFORT 600 UGR<19 PS 33W 840 U19 PS	4099854015113	4 x 18 W FL	4320/3900/3640	33/30/28	130	4000	70000	90	—	595 x 595 x 32	1
PANEL COMFORT 600 UGR<19 PS 33W 865 U19 PS	4099854015137	4 x 18 W FL	4320/3900/3640	33/30/28	130	6500	70000	90	—	595 x 595 x 32	1
PANEL COMFORT 1200 UGR<19 PS 33W 830 U19 PS	4099854004087	2 x 36 W FL	4320/3640/3120	33/28/24	130	3000	70000	90	—	1195 x 295 x 11	2
PANEL COMFORT 1200 UGR<19 PS 33W 840 U19 PS	4099854004100	2 x 36 W FL	4320/3640/3120	33/28/24	130	4000	70000	90	—	1195 x 295 x 11	2
PANEL COMFORT											
PANEL COMFORT 600 PS 28W 830 PS	4099854014192	4 x 18 W FL	3640/3250/2900	28/25/22	130	3000	70000	110	—	595 x 595 x 32	1
PANEL COMFORT 600 PS 28W 840 PS	4099854014215	4 x 18 W FL	3640/3250/2900	28/25/22	130	4000	70000	110	—	595 x 595 x 32	1
PANEL COMFORT 600 PS 33W 830 PS	4099854014864	4 x 18 W FL	4320/3900/3640	33/30/28	130	3000	70000	110	—	595 x 595 x 32	1
PANEL COMFORT 600 PS 33W 840 PS	4099854014888	4 x 18 W FL	4320/3900/3640	33/30/28	130	4000	70000	110	—	595 x 595 x 32	1
PANEL COMFORT 600 PS 33W 865 PS	4099854014901	4 x 18 W FL	4320/3900/3640	33/30/28	130	6500	70000	110	—	595 x 595 x 32	1
PANEL COMFORT 1200 PS 33W 830 PS	4099854002731	2 x 36 W FL	4320/3640/3120	33/28/24	130	3000	70000	110	—	1195 x 295 x 11	2
PANEL COMFORT 1200 PS 33W 840 PS	4099854003981	2 x 36 W FL	4320/3640/3120	33/28/24	130	4000	70000	110	—	1195 x 295 x 11	2
PANEL COMPACT											
PANEL COMPACT 600 V 35W 830 840 U19 PS	4099854206535	4 x 18 W FL	3850/3300	35/30	110	3000/4000	50000	90	—	595 x 595 x 32	1
PANEL COMPACT 625 V 35W 830 840 U19 PS	4099854206573	4 x 18 W FL	3850/3300	35/30	110	3000/4000	50000	90	—	620 x 620 x 32	1
PANEL COMPACT 600 V 35W 830 840 U19 DALI	4099854206603	4 x 18 W FL	3850	35	110	3000/4000	50000	90	DALI2	595 x 595 x 32	1
PANEL COMPACT 625 V 35W 830 840 U19 DALI	4099854206689	4 x 18 W FL	3850	35	110	3000/4000	50000	90	DALI2	620 x 620 x 32	1

¹t[h]: L70/B50 @ 25 °C (T_a)/t[h]: L80/B10 @ 25 °C (T_a) | ²All DALI luminaires support DALI-2 Energy Data (DALI part 252) and DALI-2 Diagnostic Data (DALI part 253).
³Refer to www.ledvance.com/guarantee for precise conditions