

INDUSTRY FIRST OPTI-SELECT AREA LIGHT

PERFOR-MANCE CLASS

SIMPLIFYING YOUR WORK

- OPTI-SELECT: Types III, IV and V light distribution in the same product, without opening the luminaire.
- FLEX MOUNT: Multiple mounting options included for added flexibility.
- DUAL SELECTABLE: Three wattages and three CCTs in the same luminaire.
- CONTROLS READY: Compatible with LEDVANCE standalone or networked lighting controls, no wiring required.



OPTISELECT



























ORDERING GUIDE

AREAFLD	6A	SXXX	UNH	D	SCXX	ADJ	XX
PRODUCT NAME	GENERATION	WATTAGE	VOLTAGE	DIMMING	COLOR TEMPERATURE	DISTRIBUTION	COLOR/ FINISH
AREAFLD = Area Flood	6A = Generation 6A	S080 = 40/60/80W S150 = 90/120/150W S300 = 180/240/300W	UNH = 120-347V	D = 0-10V Dimming	SC2 = 3000/4000/5000K SC15 = 1800/2200/2700K	ADJ = Adjustable T3/T4/T5	BZ = Bronze BL = Black WH = White

FEATURES





Easily accepts LEDVANCE LINK™ DLC approved Networked Lighting Control or standalone controls via screw-in receptable. Integrated 7-pin NEMA receptacle + shorting cap (optional photocell).



HOUSING

Three colors: bronze, black and white for application flexibility.

INSTALLATION MADE EASY WITH

FLEXMOUNT

Round/square pole, tenon or wall mounting included.



It is easy to recognize LEDVANCE branded luminaires with Scale Design.

FUNCTIONALITY AT IT'S FINEST WITH OPTISELECT

A revolutionary advancement in area lighting: multiple light distributions with a simple turn of a switch. No lens swap needed and no screws to remove. Eliminates concerns of water and moisture issues without requiring lens replacement.

LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone: 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

LEDVANCE is a registered trademark. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, inc. and any use of such marks by LEDVANCE LLC is under license. All other trademarks are those of their respective owners. Specifications subject to change without notice.



SCAN TO FOLLOW US ON SOCIAL MEDIA

ACCESSORIES



LEDVANCE LINK™ FIXTURE CONTROLLER W/PIR SENSOR (3.5MM) 62634



SENSOR ADAPTER FOR LEDVANCE LINK™ SENSORS 63652



MOTION SENSOR Bronze: 63748/65732 White: 62664/65622



REMOTE 65623



Spec Sheet



Install Guide