

PRODUCT DATASHEET

LS V -500/830/5/IP66

LED STRIP V 500 P | IP66 protected LED strips with 500 lm/m for general applications



Areas of application

- General indoor illumination
- General outdoor illumination
- Decorative illumination
- Private living areas

Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides
- Suitable for use in damp conditions thanks to high type of protection

Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 30,000 h at Tc max.: 75°C
- Luminous flux: 500 lm/m
- Color rendering index R_a : > 80
- Large range of color temperatures: from warm white to cool daylight
- Type of protection: IP65
- Dimmable with suitable drivers, see also www.ledvance.com/dim
- UV resistance (acc. IEC 60068-2-5)
- Salt mist resistance (acc. IEC 60068-2-52)

TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Construction wattage	24.00 W
Nominal wattage per meter	5 W
Nominal voltage	24 V
Input voltage range	23...25 V
Type of current	DC
Nominal current	1000 mA

Photometrical data

Luminous efficacy	101 lm/W ¹⁾
Luminous flux	2230 lm
Luminous flux per meter	505 lm ¹⁾
Color temperature	3000 K
Color rendering index Ra	> 80
Light color LED	Warm White
Light color (designation)	Warm White
Standard deviation of color matching	≤5 sdc _m

¹⁾ Value based on first meter of the product

Light technical data

Beam angle	120 °
Rated beam angle (half peak value)	120.00 °

LED MODULE INFORMATION

Number of LEDs per meter	70
Number of LEDs per module	350
Number of LEDs per smallest unit	7

Dimensions & Weight



Length	5000.00 mm
Length – smallest unit	100 mm

Cable length	500.000
Width	10.00 mm
Height	4.10 mm
Prewired	Yes
Conductor cross section	0.5 mm ²
LED pitch	14.29 mm
Short pitch	No
Product weight	275.00 g

Colors & materials

Cover material	Silicone
----------------	----------

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
Maximum temperature at tc test point	75 °C

Lifespan

Nominal lamp life time	30000 h
------------------------	---------

Capabilities

Dimmable	Yes ¹⁾
Lowest bending radius	30,0 mm
Self-adhesive	Yes

¹⁾ Dimmable with suitable drivers, see also www.ledvance.com/dim













Certificates & Standards













Approval marks – approval	CE / TUV
Protection class	III
Type of protection	IP66
Energy class of contained light source	F
Salt mist resistance acc. IEC 60068-2-52	Yes
UV resistance acc. IEC 60068-2-5	Yes

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------







Accessories Optional


Product image	Product name	EAN
	LS AY -CSD/P2/P	4058075727557
	LS AY -CP/P2/500/P	4058075727465
	LS AY -CSW/P2/50/P	4058075727496
	LS AY -10/SMB	4058075727618
	LS AY -10/SE/P SIL-SEAL	4058075727649
	DR DIM-PFM -60/220-240/24/P	4058075240018
	LS AY PFM -10/SE/P SIL-SEAL	4058075275744
	LS AY -PM04/UW/23X15,5/10/1	4058075278400
	LS AY -PM05/U/17,5X14,5/10/1	4058075279278
	LS AY -PM06/E/18X18/12/1	4058075279308
	LS AY -PW01/U/26X8/14/1	4058075278103
	LS AY -PW02/UW/39X26/14/1	4058075278134

Product image	Product name	EAN
	LS AY -PW03/U/26X26/14/2	4058075401501
	LS AY -PW01/U/26X8/14/2	4058075401440
	DR DIM-PFM -40/220-240/24/P	4058075239999
	LS AY -PW02/UW/39X26/14/2	4058075401471
	LS AY -PW03/U/26X26/14/1	4058075278165
	DR-VAL -30/220-240/24	4058075240056
	DR-PFM -30/220-240/24/P	4058075239890
	DR-PFM -60/220-240/24/P	4058075239913
	DR-PFM -100/220-240/24/P	4058075239937
	DR-PFM -150/220-240/24/P	4058075239975
	DR-PFM -250/220-240/24/P	4058075240032
	DR-VAL -60/220-240/24	4058075240094

Product image	Product name	EAN
	DR DIM-PFM -250/220-240/24/P	4058075240155
	DR DIM-PFM -40/220-240/24/P	4058075379176
	DR DIM-PFM -150/220-240/24/P	4058075240117
	DR DIM-PFM -100/220-240/24/P	4058075240070
	DR-VAL -120/220-240/24	4058075240131
	DR-VAL -150/220-240/24	4058075240179
	DR DIM-PFM -60/220-240/24/P	4058075379190

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	
 Legal information	LS Insert LED STRIP V IP66
 Declarations of conformity	Declaration of Conformity LS V
Photometric and lighting design files	Document name
 IES file (IES)	LS V-500-830-5-IP66
 LDT file (Eulumdat)	LS V-500-830-5-IP66
	Light distribution curve type polar LS V-500-830-5-IP66

Tender texts	Document name
 Tender documents	LED STRIP V 500 P 500 830 5 IP66-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075705463	Folding box 1	242 mm x 242 mm x 26 mm	426.00 g	1.52 dm ³
4058075705470	Shipping box 20	550 mm x 325 mm x 270 mm	8353.00 g	48.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.