

PRODUCT DATASHEET SMART+ Wifi Planon Plus Frame 300x300mm RGB + TW

SMART+ Planon Plus RGBW | Panel luminaires with WiFi technology



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data


Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	80.000 mA
Inrush current	16.1 A
Inrush current time T _{h50}	125 μs
Max. number of luminaires per miniature circuit breaker B16	37
Max. number of luminaires per miniature circuit breaker C16	47
Power factor λ	> 0.70
Total harmonic distortion	< 30 %
Protection class	П
Operating mode	Mains voltage

Photometrical data

Luminous flux	1300 lm
Total luminous flux of contained light sources	1800 lm
Luminous efficacy	72 lm/W
Color temperature	27006500 K
Light color (designation)	Tunable White / RGB
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °
UGR	< 25

Dimensions & Weight

Length	295.00 mm
Width	295.00 mm
Height	51.00 mm
Product weight	1240.00 g



SMART WIFIPLANPLUS RGBFR

Materials & Colors

Product color	White
Housing color	White
Body material	Metal
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	40000 h
Number of switching cycles	25000

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Replaceable light source (EPREL) Not replaceable	
Additional product data	
Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	SMART+ PLANON PLUS
PDF	Extended installation guide	SMART+ WIFI INSTALLATION GUIDE
PDF	Declarations of conformity	SMART WIFIPLANPLUS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075752603	Folding box 1	72 mm x 342 mm x 332 mm	1375.00 g	8.18 dm ³
4058075752610	Shipping box 4	367 mm x 302 mm x 362 mm	6092.00 g	40.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.