

PRODUCT DATASHEET SMART+ Wifi Planon Plus Frame 1200x300mm RGB + TW

SMART+ Planon Plus RGBW | Panel luminaires with WiFi technology



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

Nominal wattage	36.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	162.000 mA	
Inrush current	12.4 A	
Inrush current time T _{h50}	115 µs	
Max. number of luminaires per miniature circuit breaker B16	42	
Max. number of luminaires per miniature circuit breaker C16	42	
Power factor λ	> 0.90	
Total harmonic distortion	< 30 %	
Protection class	II .	
Operating mode	Mains voltage	

Photometrical data

Luminous flux	2800 lm
Total luminous flux of contained light sources	4000 lm
Luminous efficacy	77 lm/W
Color temperature	27006500 K
Light color (designation)	Tunable White / RGB
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °
UGR	< 25

Dimensions & Weight

Length	1195.00 mm
Width	295.00 mm
Height	51.00 mm
Product weight	3250.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Metal
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
With light source	Yes	

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	25000

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	--

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates Document name		
PDF	User instruction / safety instructions	SMART+ PLANON PLUS	
PDF	Extended installation guide	SMART+ WIFI INSTALLATION GUIDE	
PDF	Declarations of conformity	SMART WIFIPLANPLUS	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075752641	Folding box 1	72 mm x 1,242 mm x 332 mm	3685.00 g	29.69 dm ³
4058075752658	Shipping box 2	1,267 mm x 162 mm x 362 mm	8374.00 g	74.30 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.