

PRODUCT DATASHEET

DL IP44 FRAME DN 90 WT

DOWNLIGHT IP44 FRAME | Surface mounting frame for Downlight IP44



Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Shops
- Bathrooms

Product benefits

- Easily installed

Product features


- Robust polycarbonate casing
- Mounting accessories included



TECHNICAL DATA

Dimensions & Weight

Diameter	90 mm
Height	47 mm
Product weight	50.00 g



DL IP44 FRAME DN 90



Materials & Colors







Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Mounting type	Surface
Mounting location	Ceiling

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	DL IP44 FRAME DN WT
 User instruction / safety instructions	DL IP44 FRAME DN BK/WT


Documents and certificates		Document name
	Legal information	DL IP44 DN 115 8W 830 WT
	Legal information	DL IP44 DN WT
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	DL IP44 FRAME DN
	Declarations of conformity UKCA	UKCA Declaration of Conformity DOWNLIGHT IP44 DN WT
Tender texts		Document name
	Tender documents	DOWNLIGHT IP44 FRAME DN 90 WT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075709881	Folding box 1	95 mm x 53 mm x 99 mm	74.00 g	0.50 dm ³
4058075709898	Shipping box 10	279 mm x 200 mm x 115 mm	865.00 g	6.42 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



Model	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	f [mm]	g [mm]	h [mm]
DL-IP44-DN90	Ø75	Ø38	Ø90	3-25	65	40	100	170
DL-IP44-DN115	Ø90	Ø50	Ø115	3-25	65	40	100	170
DL-IP44-DN150	Ø100	Ø60	Ø150	3-25	65	40	100	170
DL-IP44-DN180	Ø114	Ø68	Ø180	3-25	65	40	100	170
DL-IP44-DN215	Ø130	Ø76	Ø215	3-25	68	40	100	170

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.