

# PRODUCT DATASHEET LED TUBE T8 EXTERNAL 1500 mm 23W 865

LED TUBE T8 EXTERNAL | LED TUBE T8 EXTERNAL for LED DRIVER EXTERNAL



#### Areas of application

- Industrial lighting (e.g. manufacturing plants, logistic centers, warehouses)
- Linear lighting for office, education, storage areas and retail
- Shops, supermarkets

#### Product benefits

- Simple upgrade to dimmable LED system
- Hassle free application, no ballast compatibility check necessary
- Shatter protection thanks to special PET coating
- No bending thanks to glass tube
- 5 years guarantee

#### **Product features**

- Designed to power only with LED DRIVER LED TUBE EXTERNAL DALI
- Lamp tube made of glass with splinter protection
- Quality dimming of 1...100 %
- High resistance to switching loads
- Suitable for ambient temperatures from -20...+50 °C





## TECHNICAL DATA


## Electrical data

Nominal wattage	23 W
Construction wattage	23.00 W
Nominal voltage	42 V
Operating mode	EXT 1)
Nominal current	550 mA
Type of current	DC
Operating frequency	0 Hz
Mains frequency	0 Hz
Total harmonic distortion	< 20 %
Power factor $\lambda$	0.90

<sup>1)</sup> Designed to power with LEDVANCE LED DRIVER LED TUBE EXTERNAL DALI  $\ensuremath{\mathsf{P}}$ 

## Photometrical data

Luminous flux	3700 lm
Luminous efficacy	161 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0,4




EPREL data spectral diagram PROF LEDr 6500K

## Light technical data

Beam angle	190 °
Warm-up time (60 %)	< 2.00 s
Starting time	< 1.0 s

# Dimensions & Weight



Overall length	1513.00 mm
Length with base excl. base pins/connection	1500.00 mm
Diameter	27.00 mm
Product weight	245.00 g

## Temperatures & operating conditions

Ambient temperature range	-20+50 °C <sup>1)</sup>
Maximum temperature at tc test point	65 °C

<sup>1)</sup> Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

# Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Single sided LED TUBE (one-sided DC input) complying with safety requirement acc. IEC 62776:2014. Safety protection against electrical shock in misuse (ECG/CCG/Mains operation).

# Capabilities

Dimmable	Yes

## Certificates & Standards

Energy efficiency class	D 1)
Energy consumption	23.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Country-specific categorizations

Order reference

LOGISTICAL DATA	
Temperature range at storage	-20+80 °C

LEDTUBE T8 EXT

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	No
Length	1513.00 mm
Height	27.00 mm
Width	27.00 mm
Chromaticity coordinate x	0,312
Chromaticity coordinate y	0,328
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0,90
Displacement factor	0,90

LED light source replaces a fluorescent light source	No
EPREL ID	1161826
Model number	AC39951,AC39951

## **Accessories Mandatory**

Product image	Product name	EAN	
	DR EXTERNAL DALI -1X15-37W 220-240	4058075730632	
1	DR EXTERNAL DALI -1X7-37W 220-240	4099854295157	
/	DR EXTERNAL DALI -2X7-26W 220-240	4099854295171	

## Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- Disconnect mains before installation.
- All electrical connections must be made by a qualified person.

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	LEDTUBE EXT P User instruction LEDV
PDF	Extended installation guide	LEDVANCE Luminaire conversion checklist
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	LEDTUBE T5 and T8
PDF	Declarations of conformity UKCA	LEDTUBE T5 and T8 EXT

Photometric and lighting design files	Document name
IES file (IES)	LEDTUBE T8 EXT P 1500 23W
IES file (IES)	LEDTUBE T8 EXT P 1500 23W 865
LDT file (Eulumdat)	LEDTUBE T8 EXT P 1500 23W
LDT file (Eulumdat)	LEDTUBE T8 EXT P 1500 23W 865
UGR file (UGR table)	LEDTUBE T8 EXT P 1500 23W
UGR file (UGR table)	LEDTUBE T8 EXT P 1500 23W 865
Light distribution curve type polar	LEDTUBE T8 EXT P 1500 23W
Light distribution curve type polar	LEDTUBE T8 EXT P 1500 23W 865
Spectral power distribution	EPREL data spectral diagram PROF LEDr 6500K

Tender texts	Document name
Tender documents	LED TUBE T8 EXTERNAL P 1500 mm 23W 865-EN

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075730571	Sleeve 1	1,520 mm x 28 mm x 28 mm	265.00 g	1.19 dm <sup>3</sup>
4058075730588	Shipping box 25	1,650 mm x 215 mm x 230 mm	7966.00 g	81.59 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For current information see www.ledvance.com/ledtube

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.