

## PRODUCT DATASHEET

### ENDURA Classic Garden Spot Spike

Endura Garden SpotSpike | Outdoor Endura Classic Garden spot spike with socket GU10



#### Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

#### Product benefits

- High flexibility in the choice of the light source thanks to GU10 socket
- Easy and quick installation
- High-quality materials

#### Product features

- Die-cast aluminum housing
- Adjustable luminaire head



TECHNICAL DATA

Electrical data

|                  |             |
|------------------|-------------|
| Nominal voltage  | 220...240 V |
| Mains frequency  | 50...60 Hz  |
| Protection class | I           |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 65.00 mm  |
| Width          | 130.00 mm |
| Height         | 415.00 mm |
| Product weight | 600.00 g  |
| Cable length   | 1500 mm   |



ENDURA CLASSIC GARDN SPOT  
SPIKE GU10

Materials & Colors

|                 |           |
|-----------------|-----------|
| Product color   | Dark gray |
| Housing color   | Dark gray |
| Body material   | Aluminum  |
| Mercury content | 0.0 mg    |

Application & Mounting

|                                        |                  |
|----------------------------------------|------------------|
| Ambient temperature range              | -20...+40 °C     |
| Type of connection                     | Plug type C (EU) |
| Type of protection                     | IP54             |
| Protection class IK (shock resistance) | IK04             |
| Dimmable                               | No               |
| Mounting type                          | Ground spike     |
| Application environment                | Outdoor          |
| Adjustable                             | Yes              |

|                          |      |
|--------------------------|------|
| With light source        | No   |
| Replaceable light source | No   |
| Holder designation       | GU10 |

### Certificates & Standards

|                                                      |    |
|------------------------------------------------------|----|
| Standards                                            | CE |
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe                                       | No |

### Additional product data

|                       |                            |
|-----------------------|----------------------------|
| Product remark        | Maximum bulb wattage: 35 W |
| Number of illuminants | 1                          |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                       |
|------------------------------------------------------------------------------------|----------------------------------------|-------------------------------------|
|  | User instruction / safety instructions | ENDURA CLASSIC GARDN SPOTSPIKE GU10 |
|  | Legal information                      | Safety insert G11219578             |
|  | Declarations of conformity             | ENDURA CLASSIC GARDN                |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854447204 | Folding box<br>1             | 102 mm x 162 mm x 222 mm             | 711.00 g     | 3.67 dm <sup>3</sup> |

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4099854447211 | Shipping box<br>4            | 340 mm x 220 mm x 250 mm             | 3244.00 g    | 18.70 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.