

PRODUCT DATASHEET ENDURA Classic Spot Square Wall

Endura Classic Spot Square | Outdoor Endura Classic spot square socket GX53



Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

Product benefits

- High flexibility in the choice of the light source thanks to GX53 base
- Easy and quick installation
- High-quality materials

Product features

- Die-cast aluminum housing
- Adjustable luminaire head



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	I

Photometrical data

Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-

Dimensions & Weight

Length	100.00 mm
Width	170.00 mm
Height	90.00 mm
Product weight	420.00 g



ENDURA CLASSIC SPOT SQUARE WALL GX53

Materials & Colors

Product color	Black	
Housing color	Black	
Body material	Aluminum Polycarbonate (PC)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Dimmable	No
Mounting type	Surface

Application environment	Outdoor
Adjustable	Yes
With light source	No
Replaceable light source	No
Holder designation	GX53

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Number of illuminants 1

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	ENDURA CLASSIC SPOT SQUARE WALL	
PDF	Legal information	Legal insert I-Outdoor	
POF	Declarations of conformity	ENDURA CLASSIC SPOT SQUARE	
PDF	Declarations of conformity UKCA	Fixed LUM without EMC	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763845	Folding box	112 mm x 172 mm x 97 mm	481.00 g	1.87 dm ³
4058075763852	Shipping box	308 mm x 190 mm x 252 mm	3220.00 g	14.75 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.