

# PRODUCT DATASHEET LED TUBE T5 HF HE35 PERFORMANCE 1449 mm 18W 840

LED TUBE T5 HF PERFORMANCE | LED tubes for electronic high frequency control gear (ECG), shatterproof



#### Areas of application

- General illumination within ambient temperatures from -20...+45  $^{\circ}\text{C}$
- Offices, public buildings
- Supermarkets and department stores
- Industry

## Product benefits

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- High luminous flux for sophisticated lighting tasks
- Also suitable for operation at low temperatures

#### Product features

- Retrofit replacement of existing T5 lamps on HF ballast installations
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- High color consistency: ≤ 5 sdcm
- Lifetime up to 60,000 h
- Low flicker according to EU 2019-2020 (SVM  $\leq$  0.4 / PstLM  $\leq$  1)
- Type of protection: IP20
- Compatible with many common electronic control gears (see also compatibility list)





# TECHNICAL DATA

## Electrical data

Nominal wattage	18 W
Construction wattage	18.00 W
Nominal voltage	105160 V
Operating mode	ECG 1)
Nominal current	210 mA
Type of current	AC
Inrush current	12 A
Operating frequency	2575 kHz
Mains frequency	2575 kHz
Max. lamp number on MCB B10 A	17
Max. lamp number on MCB B16 A	28
Total harmonic distortion	15 %
Power factor $\lambda$	> 0.90

<sup>1)</sup> Check ECG compatibility at ledvance.com/compatibility

## Photometrical data

Luminous flux	2800 lm
Luminous efficacy	155 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



EPREL data spectral diagram PROF LEDr 4000K

# Light technical data

Beam angle	190 °	
Warm-up time (60 %)	< 2.00 s	
Starting time	< 0.5 s	

# Dimensions & Weight



Overall length	1463.00 mm
Length with base excl. base pins/connection	1449.00 mm
Diameter	18.50 mm
Product weight	175.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C <sup>1)</sup>	
Maximum temperature at tc test point	70 °C	
Performance temp. acc. to IEC 62717	50 °C <sup>2)</sup>	

<sup>1)</sup> Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

# Lifespan

Lifespan L70/B50 at 25 °C	60000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70

<sup>2)</sup> Tp rated. Tp point coincides with Tc point - marked on device  $\,$ 

Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	G5
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	D 1)
Energy consumption	18.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG0
Country-specific categorizations	LEDTURE TO LICILI
Order reference	LEDTUBE T5 HF H
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G5
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE

0 W

Standby power

Networked standby power for CLS	0 W	
Claim of equivalent power	No	
Length	1463.00 mm	
Height	18.50 mm	
Width	18.50 mm	
Chromaticity coordinate x	0.382	
Chromaticity coordinate y	0.38	
R9 Colour rendering index	1	
Beam angle correspondence	SPHERE_360	
Survival factor	0.9	
Displacement factor	0.9	
LED light source replaces a fluorescent light source	No	
EPREL ID	1317798	
Model number	AC44154,AC44154	

## Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Lamp not suitable for emergency operation.

#### DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions		
PDF	Extended installation guide Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN		
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	LED TUBE T5 HF	
POF	Declarations of conformity UKCA	LED TUBE T5 HF	
PDF	ECG compatibility list	Ballast compatibility LEDVANCE LED TUBE T5 HF_T8 HF_T8 UNIVERSAL 2025	

Photometric and lighting design files	Document name	
IES file (IES)	LEDTUBE T5 HF HE35 P 1449 18W 840 LEDV	
LDT file (Eulumdat)	LEDTUBE T5 HF HE35 P 1449 18W 840 LEDV	
UGR file (UGR table)	LEDTUBE T5 HF HE35 P 1449 18W 840 LEDV	
Light distribution curve type polar	LEDTUBE T5 HF HE35 P 1449 18W 840 LEDV	
Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K	
Tender texts Docu	ment name	


Tender texts	Document name
Tender documents	LED TUBE T5 HF P 1449 mm 18W 840-EN

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854029196	Sleeve 1	1,465 mm x 20 mm x 24 mm	201.00 g	0.70 dm <sup>3</sup>
4099854029202	Shipping box 10	1,525 mm x 155 mm x 90 mm	2541.00 g	21.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



#### References / Links

- For current information see www.ledvance.com/ledtube

## Legal advice

- When used to replace a T5 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.