

# PRODUCT DATASHEET LED TUBE T8 UNIVERSAL ULTRA OUTPUT PERFORMANCE 1500 mm 23W 865

LED TUBE T8 UNIVERSAL ULTRA OUTPUT PERFORMANCE | LED tubes for electronic control gear (ECG), electromagnetic control gear (CCG) and AC mains, shatterproof



#### Areas of application

- General illumination within ambient temperatures from -20...+45  $^{\circ}\text{C}$
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores
- Industry

#### Product benefits

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- Energy savings of up to 60 % (compared to T8 fluorescent lamp)
- Very high resistance to switching loads
- High luminous flux for sophisticated lighting tasks
- Support the implementation of the HACCP concepts from production through to presentation
- Also suitable for operation at low temperatures

#### Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG, ECG luminaires or on AC mains
- Compatible with conventional and many common electronic control gears (see also compatibility list) and line voltage
- Low flicker according to EU 2019-2020 (SVM ≤ 0.4 / PstLM ≤ 1)





- Lamp tube made of glass with splinter protection
- For especially uniform illumination
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime up to 60,000 h

# TECHNICAL DATA


## Electrical data

Nominal wattage	23 W
Construction wattage	23.00 W
Nominal voltage	220240 V
Operating mode	ECG, CCG, AC Mains 1)
Nominal current	106 mA
Type of current	AC
Inrush current	7 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	70
Max. lamp number on MCB B10 A - CCG without compensation	70
Max. lamp number on MCB B10 A - CCG with compensation	28
Max. lamp number on MCB B16 A	110
Max. lamp number on MCB B16 A - CCG without compensation	110
Max. lamp number on MCB B16 A - CCG with compensation	47
Total harmonic distortion	< 30 %
Power factor $\lambda$	0.90

<sup>1)</sup> Check ECG compatibility at ledvance.com/compatibility

# Photometrical data

Luminous flux	3700 lm
Luminous efficacy	160 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	≤0.4



EPREL data spectral diagram PROF LEDr 6500K

# Light technical data

Beam angle	190 °	
Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

# Dimensions & Weight



Overall length	1513.00 mm
Length with base excl. base pins/connection	1500.00 mm
Diameter	27.80 mm
Product weight	307.00 g

# Temperatures & operating conditions

Ambient temperature range		-20+45 °C <sup>1)</sup>	
	Maximum temperature at tc test point	75 °C	
	Performance temp. acc. to IEC 62717	55 °C <sup>2)</sup>	

<sup>1)</sup> Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

## Lifespan

Lifespan L70/B50 at 25 °C	60000 h
Lifespan L80/B50 at 25 °C	60000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70

December 15, 2025, 04:31:23

LED TUBE T8 UNIVERSAL ULTRA

OUTPUT PERFORMANCE 1500 mm 23W

<sup>2)</sup> In operation with CCG/AC. Tp: 55°C in ECG operation. / Tp rated. Tp point coincides with Tc point - marked on device

Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	C 1)
Energy consumption	23.00 kWh/1000h
Type of protection	IP20
Chandarda	CE
Standards	
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo	PG0  owest efficiency)
Photobiological safety group acc. to EN62778	
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local country-specific categorizations	owest efficiency)
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo Country-specific categorizations  Order reference	owest efficiency)
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local country-specific categorizations  Order reference  LOGISTICAL DATA	owest efficiency)  LEDTUBE T8 UN U
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage	owest efficiency)  LEDTUBE T8 UN U
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015	LEDTUBE T8 UN U  -20+80 °C
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used	LEDTUBE T8 UN U  -20+80 °C
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS  G13
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS  G13  No
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS  G13  No  No
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS  G13  No  No  No  No
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations)  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS  G13  No  No  No  No  No  No  No  No  No
Photobiological safety group acc. to EN62778  1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations)  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield	LEDTUBE T8 UN U  -20+80 °C  LED  NDLS  MLS  G13  No  No  No  No  No  No  No  No  No  N

1513.00 mm

Length

Height	27.80 mm
Width	27.80 mm
Chromaticity coordinate x	0.3123
Chromaticity coordinate y	0.3283
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	`0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1317784
Model number	AC42579,AC42579

# Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- For operation of LED TUBE T8 UN with a conventional control gear, the existing starter must be exchanged with the including LED starter in the LED tube packaging.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	instructions LEDTUBE T8 UNIVERSAL Ledvance	
PDF	Extended installation guide	Notes on the operation of LEDVANCE LED tubes in compensated luminaires	
PDF	Extended installation guide	LEDVANCE Luminaire conversion checklist	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	LED TUBES T8 HF/UN	
PDF	Declarations of conformity UKCA	LED TUBES T8 HF/UN UKCA	
PDF	ECG compatibility list	Ballast compatibility LEDVANCE LED TUBE T5 HF_T8 HF_T8 UNIVERSAL 2025	

	Photometric and lighting design files Document name		
	IES file (IES)	LEDTUBE T8 UN UO P 1500 23W 865 LEDV	
	LDT file (Eulumdat)	LEDTUBE T8 UN UO P 1500 23W 865 LEDV	
	UGR file (UGR table)	LEDTUBE T8 UN UO P 1500 23W 865 LEDV	
	Light distribution curve type polar	LEDTUBE T8 UN UO P 1500 23W 865 LEDV	
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 6500K	
-			


Tender texts	Document name
Tender documents	LED TUBE T8 UNIVERSAL ULTRA OUTPUT P 1500 mm 23W 865-EN

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854026591	Sleeve 1	1,605 mm x 29 mm x 29 mm	341.00 g	1.35 dm <sup>3</sup>
4099854026607	Shipping box 10	1,652 mm x 210 mm x 115 mm	4250.00 g	39.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



## References / Links

- For current information see www.ledvance.com/ledtube

## Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

December 15, 2025, 04:31:23 LED TUBE T8 UNIVERSAL ULTRA OUTPUT PERFORMANCE 1500 mm 23W

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.