

PRODUCT DATASHEET LED TUBE T8 HF VALUE 600 mm 8W 840

LED TUBE T8 HF VALUE | Economic LED tubes for electronic high frequency control gear (ECG)



Areas of application

- General illumination within ambient temperatures from -20...+45 $^{\circ}\text{C}$
- Corridors, stairways, parking garages
- Industry
- Warehouses
- Cooling and storage rooms
- Domestic applications
- Supermarkets and department stores

Product benefits

- No bending thanks to glass tube
- Energy savings of up to 55 % (compared to T8 fluorescent lamp)
- Quick, simple and safe replacement without rewiring
- Very high resistance to switching loads
- Also suitable for operation at low temperatures

Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in ECG luminaires
- Compatible with many common electronic control gears (see also compatibility list)
- Low flicker according to EU 2019-2020 (SVM ≤ 0.4 / PstLM $\leq 1)$
- Tube made of glass
- Uniform illumination
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime up to 30,000 h





TECHNICAL DATA


Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	2540 V
Operating mode	ECG ¹⁾
Nominal current	330 mA
Type of current	AC
Inrush current	24 A
Operating frequency	3575 kHz
Mains frequency	3575 kHz
Max. lamp number on MCB B10 A	17
Max. lamp number on MCB B16 A	28
Total harmonic distortion	< 15 %
Power factor λ	0.80

¹⁾ Check ECG compatibility at ledvance.com/compatibility

Photometrical data

Luminous flux	900 lm
Luminous efficacy	112 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	≤0.4



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	190°
Warm-up time (60 %)	< 2.00 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	603.00 mm
Length with base excl. base pins/connection	600.00 mm
Diameter	27.80 mm
Product weight	137.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹⁾
Maximum temperature at tc test point	65 °C
Performance temp. acc. to IEC 62717	55 °C ²⁾

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Lifespan L80/B50 at 25 °C	30000 h
Number of switching cycles	200000

December 13, 2025, 07:56:32 LED TUBE T8 HF VALUE 600 mm 8W 840

²⁾ Tp rated. Tp point coincides with Tc point - marked on device $\,$

	PRODUCT DATASHE
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
·	No
Dimmable	No F 1)
Dimmable Certificates & Standards	
Dimmable Certificates & Standards Energy efficiency class	F 1)
Dimmable Certificates & Standards Energy efficiency class Energy consumption	F ¹⁾ 8.00 kWh/1000h

Country-specific categorizations

Order reference

LOGISTICAL DATA	
Temperature range at storage	-20+80 °C

LEDTUBE T8 HF V

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No

December 13, 2025, 07:56:32 LED TUBE T8 HF VALUE 600 mm 8W 840

Length	603.00 mm
Height	27.80 mm
Width	27.80 mm
Chromaticity coordinate x	0.3818
Chromaticity coordinate y	0.3797
R9 Colour rendering index	` 0
Beam angle correspondence	SPHERE_360
Survival factor	` 0.9
Displacement factor	0.8
LED light source replaces a fluorescent light source	No
EPREL ID	1317764
Model number	AC42574

Safety advice

- Not suitable for operation with low-loss and conventional control gears and main voltage.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	LEDTUBE T8 HF Ledvance
POF	Extended installation guide	Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN
POF	Legal information	Informationstext 18 Abs 4 ElektroG
POF	Declarations of conformity	LED TUBES T8 HF/UN
PDF	Declarations of conformity UKCA	LED TUBES T8 HF/UN UKCA
PDF	ECG compatibility list	Ballast compatibility LEDVANCE LED TUBE T5 HF_T8 HF_T8 UNIVERSAL 2025

Photometric and lighting design files	Document name
IES file (IES)	LEDTUBE T8 HF V 600 8W 840 LEDV
LDT file (Eulumdat)	LEDTUBE T8 HF V 600 8W 840 LEDV
UGR file (UGR table)	LEDTUBE T8 HF V 600 8W 840 LEDV
Light distribution curve type polar	LEDTUBE T8 HF V 600 8W 840 LEDV
Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K
Tender texts Docu	ment name

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854026256	Sleeve 1	610 mm x 31 mm x 31 mm	155.00 g	0.59 dm ³
4099854026263	Shipping box 10	662 mm x 210 mm x 115 mm	1910.00 g	15.99 dm ³

LED TUBE T8 HF V 600 mm 8W 840-EN

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

Tender documents



References / Links

- For current information see www.ledvance.com/ledtube

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.