

PRODUCT DATASHEET LED TUBE T8 36 EM MOTION SENSOR 1200 mm 13.1W 840

LED TUBE T8 EM MOTION SENSOR | LED tubes with integrated microwave sensor for electromagnetic control gear (CCG), shatterproof



Areas of application

- General illumination within ambient temperatures from -20...+50 °C
- Corridors, stairways, parking garages
- Domestic applications
- Secondary rooms, garages, storerooms, cellars

Product benefits

- Energy savings of up to 67 % compared to conventional fluorescent lamp
- Quick, simple and safe replacement of fluorescent lamps
- Suitable for closed luminaires thanks to microwave technology
- No bending thanks to glass tube
- Shatter protection thanks to special PET coating
- Very high resistance to switching loads
- Also suitable for operation at low temperatures

Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires
- Integrated microwave sensor with motion detection
- Automatic dimming to 20 % light output after 5 minutes without motion detection





- Automatic light switch off 7 minutes after the last motion detection
- Microwave sensor with 5,8 GHz
- Motion detection up to 5 m

TECHNICAL DATA

Electrical data

| Nominal wattage | 13.1 W |
|--|---|
| Construction wattage | 13.10 W |
| Nominal voltage | 220240 V |
| Operating mode | Conventional control gear (CCG), AC Mains |
| Nominal current | 60 mA |
| Type of current | AC |
| Inrush current | 5.10 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 117 |
| Max. lamp number on MCB B10 A - CCG without compensation | 117 |
| Max. lamp number on MCB B10 A - CCG with compensation | 18 |
| Max. lamp number on MCB B16 A | 147 |
| Max. lamp number on MCB B16 A - CCG without compensation | 147 |
| Max. lamp number on MCB B16 A - CCG with compensation | 24 |
| Total harmonic distortion | < 20 % |
| Power factor λ | > 0.90 |

Photometrical data

| Luminous flux | 2100 lm |
|---|------------|
| Luminous efficacy | 160 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | ≥80 |
| Light color | 840 |
| Standard deviation of color matching | ≤5 sdcm |
| Rated LLMF at 6,000 h | 0.80 |
| Flickering metric (Pst LM) | 1 |
| Stroboscope effect metric (SVM) | 0.4 |



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

| Beam angle | 190 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| Overall length | 1212.00 mm |
|---|------------|
| Length with base excl. base pins/connection | 1200.00 mm |
| Diameter | 26.70 mm |
| Product weight | 200.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+50 °C ¹⁾ |
|--------------------------------------|-------------------------|
| Maximum temperature at tc test point | 70 °C |

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

| Lifespan L70/B50 at 25 °C | 60000 h |
|--|---------|
| Number of switching cycles | 200000 |
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

December 12, 2025, 20:31:16

LED TUBE T8 36 EM MOTION SENSOR
1200 mm 13.1W 840

Additional product data

| Base (standard designation) | G13 |
|-----------------------------|--------|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |

Capabilities

| Dimmable | No |
|----------|----|
| | |

Certificates & Standards

| Energy efficiency class | C 1) |
|--|-----------------|
| Energy consumption | 14.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG0 |

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

| Order reference | LEDTUBE T8 36 E |
|-----------------|-----------------|
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| Lighting technology used | LED |
|---|--------------|
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | G13 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Standby power | 0 W |
| Claim of equivalent power | No |
| Length | 1212.00 mm |
| Height | 26.70 mm |
| Width | 26.70 mm |
| Chromaticity coordinate x | 0,3818 |
| | |

| 0.3797 |
|-----------------|
| 1 |
| SPHERE_360 |
| 0.9 |
| 0.9 |
| No |
| 1351268 |
| AC45303,AC45303 |
| |

EQUIPMENT / ACCESSORIES

- Suitable for operation with low-loss and conventional control gears

Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- Recommended maximum mounting height: 5 m
- Not suitable for emergency lighting.
- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|--|---|--|
| PDF | User instruction / safety instructions | LEDTUBE T8 EM MS | |
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG | |
| PDF | Legal information | Safety insert_G11243847 | |
| PDF | Declarations of conformity | LEDTUBE T8 EM MS | |
| PDF | Declarations of conformity UKCA | LEDTUBE T8 EM MS | |
| | | | |
| | Photometric and lighting design files | Document name | |
| | Spectral power distribution | EPREL data spectral diagram PROF LEDr 4000K | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854045301 | Sleeve 1 | 27 mm x 27 mm x 1,310 mm | 277.00 g | 0.95 dm ³ |
| 4099854045318 | Shipping box 8 | 1,340 mm x 155 mm x 95 mm | 2794.00 g | 19.73 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/osram-led-tube

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.