

PRODUCT DATASHEET SMART+ WIFI OUTDOOR TERMINAL EU

SMART+ OUTDOOR TERMINAL | Outdoor Terminal with integrated WiFi Repeater and two Smart Sockets



Areas of application

- Wherever non-smart devices need to be integrated into compatible smart home systems
- Gardens, balconies and other outdoor areas

Product benefits

- Integrated WiFi Repeater extends the WLAN zone up to 45 meter in open air
- WiFi Repeater enables pairing of other wireless devices to WLAN upto 15 devices
- High standard of safety: Overload protection, Surge protection
- Integrates conventional electric equipment into compatible smart home systems
- Enables remote switching of conventional light sources and other electric devices

Product features

- Voice control available: Google Assistant and Amazon Alexa
- Two smart standard sockets can be controlled individually
- $-\,$ High switching power: up to 3,680 W / 16 A
- Network protocol: WiFi (2.4 GHz)
- Type of protection: IP44
- Scheduling
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)



TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Nominal current	16 A
Mains frequency	50 Hz

Dimensions & Weight



Product weight	1770.00 g
Length	164.00 mm
Width	140.00 mm
Height	325.00 mm
Lifespan	
Number of switching cycles	10000

Colors & materials

Product color	Anthracite
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20+35 °C

Capabilities

Dimmable	No
Type of connection	Power cable/Plug
Compatible smart home technology	Amazon Alexa / Google Home

Certificates & Standards

Standards	CE
Protection class	1
Type of protection	IP44

EQUIPMENT / ACCESSORIES

- Ground spike included for easy fixation in garden soil
- 3 meter power cable for flexible installation
- Cable connector included if the power cord needs to be prolonged
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the SMART+ Outdoor Terminal, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Outdoor Terminal in conjunction with medical equipment.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SMART OUTDOOR TERMINAL EU	
PDF	Declarations of conformity	CE Declaration SMART WIFI OUTDOOR TERMINAL	
PDF	EU Data Act	SMART WiFi Plugs	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854025570	Folding box	212 mm x 347 mm x 147 mm	2130.00 g	10.81 dm ³
4099854025587	Shipping box 4	447 mm x 367 mm x 324 mm	9130.00 g	53.15 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/en-int/home-lighting/services/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.