

PRODUCT DATASHEET QBM 220-240 LS-PD CM KIT

LS PD CM KIT | Mounting kits





Areas of application

- Open offices
- Individual offices
- Conference rooms
- Classrooms
- Storage and break areas
- Stairways
- Toilets
- Entrance halls
- Industry
- Production halls

Product benefits


- Enables surface and recessed ceiling mounting

Product features

- Surface mounting box
- Recessed ceiling spring clips

TECHNICAL DATA

Dimensions & Weight



Length	66.00 mm
Mounting hole spacing, length	68.00 mm
Width	66.00 mm
Height	43.50 mm
Diameter	66.00 mm
Product weight	80.00 g

Colors & materials

Product color	White

Temperatures & operating conditions

Ambient temperature range	-20+45 °C
7 timborit tomporatare range	201 10 0

Capabilities

Dimmable	No
Type of installation	Surface mounting

Certificates & Standards

Approval marks – approval	CE / UKCA
Protection class	П
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Suitable for QBM 220-240 LS/PD CI and QBM 220-240 LS/PD HB CI

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	QBM 220-240 LS/PD

	Documents and certificates	Document name
POF	Declarations of conformity	QBM 220-240 LS/PD
PDF	Declarations of conformity UKCA	QBM 220-240 LS/PD

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172161466	Folding box	110 mm x 110 mm x 100 mm	144.00 g	1.21 dm ³
4062172161473	Shipping box 48	630 mm x 460 mm x 244 mm	8032.00 g	70.71 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.