

PRODUCT DATASHEET LED PIN 60 320° P 4.9W 840 Clear G9

LED PIN G9 P | LED lamps with retrofit pin base G9



Areas of application

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Good all-around light emission
- Long lifetime of up to 15,000 h
- Four year guarantee
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to conventional high voltage lamps






TECHNICAL DATA

Electrical data

| Nominal wattage | 4.9 W |
|--|----------|
| Construction wattage | 4.90 W |
| Nominal voltage | 220240 V |
| Operating mode | AC Mains |
| Claimed equiv. conventional lamp power | 60 W |
| Nominal current | 40 mA |
| Type of current | AC |
| Inrush current | 7.1 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 84 |
| Max. lamp number on MCB B16 A | 105 |
| Total harmonic distortion | 133 % |
| Power factor λ | > 0.40 |

Photometrical data

| Luminous flux | 806 lm |
|---|------------|
| Luminous efficacy | 164 lm/W |
| Lumen main.fact.at end of nom.life time | 0.93 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | 80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdcm |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.4 |




349924_4000K_Se_5630.eps

Light technical data

| Beam angle | 320 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| Overall length | 59.00 mm |
|------------------|----------|
| Diameter | 18.00 mm |
| Maximum diameter | 18 mm |
| Product weight | 11.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---|--|
| rimum temperature at tc test point 94.7 °C | |
| Lifespan | |
| Lifespan L70/B50 at 25 °C | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.93 |
| Additional product data | |
| Base (standard designation) | G9 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
| Capabilities | |
| Dimmable | No |
| Certificates & Standards | |
| Energy efficiency class | C 1) |
| Energy consumption | 5.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG1 |
| Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (I Country-specific categorizations | owest efficiency) |
| Order reference | LED PIN60 4.9W |
| LOGISTICAL DATA | |
| Temperature range at storage | -20+80 °C |
| Energy labelling regulation data acc EU 2019/2015 | |
| Lighting technology used | LED |
| | |

NDLS

Non-directional or directional

| Mains or non-mains | MLS |
|--|-------------------------|
| Light source cap-type (or other electric interface) | G9 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Standby power | 0 W |
| Claim of equivalent power | Yes |
| Length | 59.00 mm |
| Height | 18.00 mm |
| Width | 18.00 mm |
| Chromaticity coordinate x | 0.3818 |
| Chromaticity coordinate y | 0.3797 |
| R9 Colour rendering index | 1 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.9 |
| Displacement factor | 0.5 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 2005324,2365052 |
| Model number | AC64392,AC64392,AC84154 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|----------------------------|---------------|
| PDF | Declarations of conformity | LED PIN 60 |
| PDF | Declarations of conformity | LED lamp |

| | Documents and certificates Document name | | |
|-----|--|--------------------------|--|
| PDF | Declarations of conformity UKCA | LED PIN60 | |
| PDF | Declarations of conformity UKCA | LED lamp | |
| | | | |
| | Photometric and lighting design files | Document name | |
| | Spectral power distribution | 349924_4000K_Se_5630.eps | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075840584 | Folding box 1 | 28 mm x 28 mm x 67 mm | 16.00 g | 0.05 dm ³ |
| 4058075840591 | Shipping box 20 | 150 mm x 122 mm x 77 mm | 356.00 g | 1.41 dm ³ |
| 4099854329036 | Shipping box 120 | 256 mm x 160 mm x 248 mm | 2271.00 g | 10.16 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.