

PRODUCT DATASHEET Smart+ Wifi Undercabinet Select 7W

SMART+ WIFI UNDERCABINET SELECT SENSOR | Undercabinet luminaire with selectable steering mode: Smart Wifi, on/off, or light motion sensor

Areas of application

- Shelf and undercabinet lighting



- Adjustable room atmosphere thanks to dimming and adjustable light color (3000-6500K)
- Allows for energy savings and comfortable operation due to sensor control

Product features

- 3 operating modes selectable: Smart Wifi, PIR Sensor, On/Off
- Luminous flux: up to 500 lm
- Network protocol: WiFi
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable



TECHNICAL DATA

Electrical data

| Nominal wattage | 9.00 W |
|---|-----------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 52.000 mA |
| Inrush current | 21,6 A |
| Inrush current time T _{h50} | 3,92 µs |
| Max. number of luminaires per miniature circuit breaker B16 | 34 |
| Max. number of luminaires per miniature circuit breaker C10 | 27 |
| Max. number of luminaires per miniature circuit breaker C16 | 44 |
| Power factor λ | > 0.5 |
| Total harmonic distortion | < 60 % |
| Protection class | II |

Photometrical data

| Luminous flux | 500 lm |
|--|---------------|
| Total luminous flux of contained light sources | 580 lm |
| Luminous efficacy | 55 lm/W |
| Color temperature | 30006500 K |
| Light color (designation) | Tunable White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | ≤6 sdcm |
| Flickering metric (Pst LM) | ≤ 1 |
| Stroboscope effect metric (SVM) | ≤ 0.4 |
| Photobiological safety group acc. to EN62778 | RG0 |
| Beam angle | 120 ° |
| UGR | < 33 |

Dimensions & Weight

| Length | 305.00 mm |
|----------------|-----------|
| Width | 61.00 mm |
| Height | 23.00 mm |
| Product weight | 224.00 g |
| Cable length | 1500 mm |



SMART WIFI UNDERCABINET SEL SEN TW

Materials & Colors

| Product color | White |
|--|--------------------|
| Housing color | White |
| Body material | Polycarbonate (PC) |
| Cover material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|------------------------------|---------------------------|
| Temperature range at storage | -20+80 °C |
| Type of connection | Plug type C (EU) |
| Type of protection | IP20 |
| Dimmable | Yes |
| Mounting type | Surface |
| Mounting location | Wall / Cabinet undersides |
| Application environment | Indoor |
| Adjustable | No |
| With light source | Yes |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h |
|----------------------------|---------|
| Number of switching cycles | 15000 |

Sensor

| Type of sensor | Motion |
|----------------------------------|---------|
| Detection range of motion sensor | < 70 mm |

Certificates & Standards

| Standards | CE |
|-----------|----|
| | |

| Luminaire with limited surface temperature, "D sign" | No |
|--|-----------------|
| Replaceable light source (EPREL) | Not replaceable |
| | |

Additional product data

| Product remark | Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
|-----------------------|---|
| Number of illuminants | empty |

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

- External mains adapter (cable length: 1.5 m) included
- Mounting clips included

Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|--|---|
| POF | User instruction / safety instructions | UI SMART+ WIFI LINEAR LED SLIM SENSOR |
| POF | Legal information | SMART WIFI UNDERCABINET SEL SEN TW |
| POF | Declarations of conformity | CE Declaration SMART WIFI UNDERCABINET SEL SEN TW |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854096532 | Folding box 1 | 56 mm x 78 mm x 404 mm | 331.00 g | 1.76 dm ³ |
| 4099854096549 | Shipping box 4 | 450 mm x 170 mm x 140 mm | 1607.00 g | 10.71 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.