

PRODUCT DATASHEET

Spot Twist 70mm 5W 3000K White White

LED SPOT RECESS TWIST PRO | Recessed spotlight with LED integrated



Areas of application

- Indoor applications
- General illumination

Product benefits

- Energy savings of up to 90 % compared to halogen lamp spotlights
- Easy installation and electrical connection thanks to tool-free electrical connectors

Product features

- Silicon-pad protected springs



TECHNICAL DATA

Electrical data

Nominal wattage	5.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	50.000 mA
Inrush current	< 15 A
Inrush current time T_{h50}	10 μ s
Max. number of luminaires per miniature circuit breaker B16	250
Max. number of luminaires per miniature circuit breaker C10	150
Max. number of luminaires per miniature circuit breaker C16	250
Power factor λ	≥ 0.5
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	400 lm
Luminous efficacy	80 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdcn
Luminous intensity	1150
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0,4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	30 °

Dimensions & Weight

Diameter	70.00 mm
Height	77.00 mm
Product weight	155.00 g

SPOT TWIST 70MM 5W

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+45 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screw terminal, 2-Pole (L,N)
Type of protection	IP20/IP20
Protection class IK (shock resistance)	IK02
Dimmable	No
Mounting type	Recessed
Mounting diameter	65 mm
Mounting depth	100 mm
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	105 mA
ECG - Length	82 mm
ECG - Width	35 mm
ECG - Height	25 mm

Certificates & Standards

Standards	CE / UKCA
-----------	-----------

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Number of illuminants	empty
-----------------------	-------




EQUIPMENT / ACCESSORIES



- Connector box not included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	UI Spot Twist
	Declarations of conformity	CE Declaration Spot Twist
	Declarations of conformity UKCA	UKCA Declaration Spot Twist

Photometric and lighting design files		Document name
	IES file (IES)	SPOT TWIST 70MM 5W 830 WT WT
	LDT file (Eulumdat)	SPOT TWIST 70MM 5W 830 WT WT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854089022	Folding box 1	89 mm x 104 mm x 104 mm	194.00 g	0.96 dm ³
4099854089039	Shipping box 20	530 mm x 230 mm x 205 mm	4326.00 g	24.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.