

## PRODUCT DATASHEET

### Vintage 1906 Big Globe 220 15 Filament 4.5W 818 Smoke E27

Vintage 1906® LED SPECIAL Shapes | LED lamps, vintage edition, special bulb shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

#### Product features

- LED lamps for line voltage
- Lamp made of glass
- Lifetime up to 15,000 h
- Beam angle: up to 360°
- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity




TECHNICAL DATA

Electrical data

|                                        |             |
|----------------------------------------|-------------|
| Nominal wattage                        | 4.5 W       |
| Construction wattage                   | 4.50 W      |
| Nominal voltage                        | 220...240 V |
| Operating mode                         | AC Mains    |
| Claimed equiv. conventional lamp power | 15 W        |
| Nominal current                        | 38 mA       |
| Type of current                        | AC          |
| Inrush current                         | 2.725 A     |
| Operating frequency                    | 50/60 Hz    |
| Mains frequency                        | 50/60 Hz    |
| Max. lamp number on MCB B10 A          | 210         |
| Max. lamp number on MCB B16 A          | 275         |
| Total harmonic distortion              | ≤180 %      |
| Power factor λ                         | ≥ 0.40      |

Photometrical data

|                                         |                    |
|-----------------------------------------|--------------------|
| Luminous intensity                      | not applicable     |
| Luminous flux                           | 150 lm             |
| Luminous efficacy                       | 33 lm/W            |
| Lumen main.fact.at end of nom.life time | 0.93               |
| Light color (designation)               | Comfort warm white |
| Color temperature                       | 1800 K             |
| Color rendering index Ra                | 80                 |
| Light color                             | 818                |
| Standard deviation of color matching    | ≤9 sdcn            |
| Flickering metric (Pst LM)              | ≤1                 |
| Stroboscope effect metric (SVM)         | ≤ 0.4              |



Spectral graph Vintage 1800 K

Light technical data

|                     |         |
|---------------------|---------|
| Beam angle          | 150 °   |
| Warm-up time (60 %) | 0.50 s  |
| Starting time       | < 0.5 s |

Dimensions & Weight

|                  |           |
|------------------|-----------|
| Overall length   | 225.00 mm |
| Diameter         | 220.00 mm |
| Maximum diameter | 220 mm    |
| Product weight   | 275.00 g  |

Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 45.6 °C      |

Lifespan

|                                              |         |
|----------------------------------------------|---------|
| Lifespan L70/B50 at 25 °C                    | 15000 h |
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.93    |

Additional product data

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base (standard designation) | E27                                                                                                                                                                                                                                                                                                                                          |
| Mercury content             | 0.0 mg                                                                                                                                                                                                                                                                                                                                       |
| Mercury-free                | Yes                                                                                                                                                                                                                                                                                                                                          |
| Design / version            | Clear                                                                                                                                                                                                                                                                                                                                        |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                                              |                 |
|----------------------------------------------|-----------------|
| Type of protection                           | IP20            |
| Standards                                    | CE / UKCA / EAC |
| Photobiological safety group acc. to EN62778 | RG1             |

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | 1906LBGL220 4,5 |
|-----------------|-----------------|

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                      |            |
|------------------------------------------------------|------------|
| Lighting technology used                             | LED        |
| Non-directional or directional                       | NDLS       |
| Mains or non-mains                                   | MLS        |
| Light source cap-type (or other electric interface)  | E27        |
| Connected light source (CLS)                         | No         |
| Color-tuneable light source                          | No         |
| Envelope                                             | No         |
| High luminance light source                          | No         |
| Anti-glare shield                                    | No         |
| Standby power                                        | 0 W        |
| Claim of equivalent power                            | Yes        |
| Length                                               | 225.00 mm  |
| Height                                               | 220.00 mm  |
| Width                                                | 220.00 mm  |
| R9 Colour rendering index                            | 1          |
| Beam angle correspondence                            | SPHERE_360 |
| Survival factor                                      | 0.9        |
| Displacement factor                                  | ≥ 0.5      |
| LED light source replaces a fluorescent light source | No         |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

| Documents and certificates                                                        |                                 | Document name                 |
|-----------------------------------------------------------------------------------|---------------------------------|-------------------------------|
|  | On-Pack-Info                    | ELR - exempt lamps            |
|  | Declarations of conformity      | LED Lamp                      |
|  | Declarations of conformity UKCA | LED lamp                      |
| Photometric and lighting design files                                             |                                 | Document name                 |
|  | Spectral power distribution     | Spectral graph Vintage 1800 K |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075836167 | Folding box<br>1             | 244 mm x 244 mm x 319 mm             | 482.00 g     | 18.99 dm³ |
| 4058075836174 | Shipping box<br>4            | 505 mm x 505 mm x 352 mm             | 3030.00 g    | 89.77 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.