

# PRODUCT DATASHEET Sun@Home Panan Desk Disc Inductive Charging Black

Sun@Home Panan Desk Disc | Table luminaire with Human Centric Lighting technology



#### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

#### Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation
- High quality metal housing
- Touch panel to adjust color temperature and dimming
- Inductive charging area on the base
- Providing both direct and indirect light

#### **Product features**



- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum
- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

# TECHNICAL DATA

# Electrical data

| Nominal wattage  | 20.00 W       |
|--|---------------|
| Nominal voltage  | 220240 V      |
| Mains frequency  | 5060 Hz       |
| Nominal current  | 75 mA         |
| Inrush current   | 2.5 A         |
| Inrush current time T <sub>h50</sub>   | 127 µs        |
| Max. number of luminaires per miniature circuit breaker B16  | 142           |
| Max. number of luminaires per miniature circuit breaker C10  Max. number of luminaires per miniature circuit breaker C16 | 133           |
|  | 213           |
| Power factor $\lambda$   | > 0.70        |
| Total harmonic distortion  | ≤ 20 %        |
| Protection class   | П             |
| Operating mode   | Mains voltage |

# Photometrical data

| Luminous flux  | 450 lm        |
|--|---------------|
| Total luminous flux of contained light sources               | 1200 lm       |
| Luminous efficacy  | 33 lm/W       |
| Color temperature  | 22005000 K    |
| Reference control setting of contained light source (Kelvin) | 2700 K        |
| Light color (designation)                                    | Tunable White |
| Color rendering index Ra                                     | > 95          |
| Standard deviation of color matching                         | ≤6 sdcm       |
| Flickering metric (Pst LM)                                   | ≤ 1 %         |
| Stroboscope effect metric (SVM)                              | ≤ 0.4 %       |
| Photobiological safety group acc. to EN62778                 | RG0           |
| Beam angle   | 120 °         |

# Dimensions & Weight

| Length         | 200.00 mm |
|----------------|-----------|
| Width          | 535.00 mm |
| Height         | 495.00 mm |
| Product weight | 3000.00 g |



# Materials & Colors

| Product color                              | Black              |
|--|--------------------|
| Housing color                              | Black              |
| Body material                              | Plastic METAL      |
| Cover material                             | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

# **Application & Mounting**

| Ambient temperature range              | -20+40 °C        |
|--|------------------|
| Temperature range at storage           | -20+80 °C        |
| Type of connection                     | Plug type C (EU) |
| Type of protection                     | IP20             |
| Protection class IK (shock resistance) | IK03             |
| Dimmable                               | Yes              |
| Type of dimming                        | WiFi             |
| Mounting type                          | Standing         |
| Mounting location                      | Table            |
| Application environment                | Indoor           |
| Adjustable                             | Yes              |
| With light source                      | Yes              |

# Lifespan

| Lifespan L70/B50 at 25 °C  | 30000 h |
|----------------------------|---------|
| Number of switching cycles | 15000   |

## Certificates & Standards

| Standards | CE / EAC |
|-----------|----------|

| Not replaceable  |  |
|--|--|
|  |  |
| Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |  |
| empty  |  |
|  |  |

## **EQUIPMENT / ACCESSORIES**

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

#### Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

#### **DOWNLOAD DATA**

| Documents and certificates   |  | Document name                    |  |
|--|--|----------------------------------|--|
| PDF  | User instruction / safety instructions   | SUNATHOME PANAN DESK DISC TW ICH |  |
| PDF Legal information  |  | Legal Insert                     |  |
| Declarations of conformity  CE Declaration Sunathome Panan Desk Disc | CE Declaration Sunathome Panan Desk Disc |                                  |  |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854109522 | Folding box<br>1             | 87 mm x 975 mm x 283 mm              | 3445.00 g    | 24.01 dm <sup>3</sup> |
| 4099854109539 | Shipping box                 | 990 mm x 300 mm x 285 mm             | 11496.00 g   | 84.65 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.