

# PRODUCT DATASHEET Endura Classic Amber Wall E27 Dark Gray

Endura Classic Amber | Bollard and wall luminaires with dark grey stainless steel and aluminum housing and E27 socket



## Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways
- Gardens and other outdoor areas

## **Product benefits**

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

## Product features

- Aluminium housing
- Type of protection: IP44

## **TECHNICAL DATA**

## Electrical data

| Nominal voltage  | 220240 V      |
|------------------|---------------|
| Mains frequency  | 5060 Hz       |
| Protection class | I             |
| Operating mode   | Mains voltage |

# **Dimensions & Weight**

| Length         | 116.00 mm |
|----------------|-----------|
| Width          | 155.00 mm |
| Height         | 295.00 mm |
| Product weight | 595.00 g  |



ENDURA CLASSIC AMBER WALL E27 DG

## Materials & Colors

| Product color                              | Dark gray          |
|--|--------------------|
| Housing color                              | Dark gray          |
| Body material                              | Aluminum           |
| Cover material                             | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |

# Application & Mounting

| Ambient temperature range              | -20+40 °C                   |
|--|-----------------------------|
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP44                        |
| Protection class IK (shock resistance) | IK03                        |
| Dimmable                               | No                          |
| Mounting type                          | Surface                     |
| Application environment                | Outdoor                     |
| With light source                      | No                          |
| Replaceable light source               | No                          |
| Holder designation                     | E27                         |

#### Certificates & Standards

| Standards  | CE / UKCA |
|--|-----------|
| Luminaire with limited surface temperature, "D sign" | No        |

### Additional product data

| Product remark        | Maximum bulb wattage: 20W (12W LED) |
|-----------------------|-------------------------------------|
| Number of illuminants | 1                                   |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## DOWNLOAD DATA

|     | Documents and certificates             | Document name                   |  |
|-----|--|---------------------------------|--|
| POF | User instruction / safety instructions | ENDURA CLASSIC AMBER            |  |
| POF | Legal information                      | Legal insert I-Outdoor          |  |
| POF | Declarations of conformity             | CE Declaration ENDURA CLASSIC   |  |
| PDF | Declarations of conformity UKCA        | UKCA Declaration ENDURA CLASSIC |  |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075835061 | Folding box<br>1             | 112 mm x 172 mm x 313 mm             | 723.00 g     | 6.03 dm <sup>3</sup>  |
| 4058075835078 | Shipping box<br>4            | 360 mm x 240 mm x 338 mm             | 2956.00 g    | 29.20 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.