

PRODUCT DATASHEET

LDVAL BATTEN 1200 13W 865

LINKABLE BATTEN | Linkable batten with a super slim, lightweight design and integral driver



Areas of application

- Offices
- Residential interiors
- Hotels, restaurants, shops

Product benefits

- Value for money luminaire
- Mercury-free technology
- Accessories for flexible mounting options included

Product features

- Protection class: II
- Color rendering index $R_a: \geq 80$
- Type of protection: IP20
- Lifetime up to 15,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	13.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.5
Protection class	II

Photometrical data

Luminous flux	1300 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Beam angle	100 °

Dimensions & Weight

Length	1185.00 mm
Width	20.00 mm
Height	31.00 mm
Product weight	230.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic

Application & Mounting

Ambient temperature range	-10...+40 °C
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	15000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854115073	Folding box 1	1,195 mm x 50 mm x 43 mm	390.00 g	2.57 dm³
4099854115080	Shipping box 30	1,210 mm x 275 mm x 285 mm	12842.00 g	94.83 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.