

PRODUCT DATASHEET WP BATTEN 1200 20-40W TRI MS

TRI COLOUR MULTI WATTAGE WEATHERPROOF BATTEN | Damp-proof luminaires



Areas of application

- Car parks
- Storage rooms
- Outdoor applications
- Passages, underpasses
- Workshops, assembly lines

Product features

- Available in 3 length options: 600 mm, 1200 mm, 1500 mm
- TRI CCT (3000K/4000K/6500K)
- Beam angle: 120°
- High luminous efficacy: up to 120 lm/W
- Type of protection: IP65
- Impact resistance: IK08
- Polycarbonate housing
- Lifetime up to 50,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz

Photometrical data

Luminous efficacy	110 lm/W	
Light color (designation)	Warm White / Cool White / Cool Daylight	
Color rendering index Ra	80	

Dimensions & Weight

Length	1265.00 mm
Width	115.00 mm
Height	86.00 mm
Product weight	1955.00 g

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP65
Dimmable	No
Mounting type	Surface
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854212673	Folding box	1,272 mm x 120 mm x 90 mm	2080.00 g	13.74 dm ³
4099854212680	Shipping box 6	1,387 mm x 250 mm x 282 mm	13480.00 g	97.78 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.