

PRODUCT DATASHEET

Orbis Concrete 300MM 13W 830 Click Dim Gray

Orbis Concrete | LED ceiling luminaire with concrete ring



Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Stylish and modern design
- Long lifetime thanks to LED technology

Product features

- Type of protection: IP20
- Lifetime up to 30,000 h
- Click-DIM version: dimmable in three steps by repeated switching
- Housing material: concrete



TECHNICAL DATA

Electrical data


Nominal wattage	13.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	80.000 mA
Inrush current	0.07 A
Inrush current time T_{h50}	26.4 μ s
Max. number of luminaires per miniature circuit breaker B16	182
Max. number of luminaires per miniature circuit breaker C10	114
Max. number of luminaires per miniature circuit breaker C16	182
Power factor λ	> 0.5
Total harmonic distortion	< 70 %
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	800 lm
Total luminous flux of contained light sources	1590 lm
Luminous efficacy	62 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤ 6 sdc _m
Flickering metric (Pst LM)	≤ 1.0
Stroboscope effect metric (SVM)	≤ 0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	116 °

Dimensions & Weight

Diameter	300.00 mm
Height	90.00 mm
Product weight	2520.00 g



ORBIS CONCRETE 300 13W830
CLICKD

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Concrete
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	3 DIM
Mounting type	Surface
Mounting location	Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	ORBIS CONCRETE 830 CLICKDIM
	Legal information	Legal insert residential luminaires
	Declarations of conformity	ORBIS CONCRETE
	Declarations of conformity UKCA	ORBIS CONCRETE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854278761	Folding box 1	135 mm x 350 mm x 350 mm	3114.00 g	16.54 dm ³
4099854278778	Shipping box 2	368 mm x 288 mm x 375 mm	6901.00 g	39.74 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

