

PRODUCT DATASHEET

LISOEV 330 SQ 19W 830 840 SF FLAT

SURFACE FLAT LIGHT SOURCES | Upgrade or replacement lightsource

Areas of application

- Suitable for SURFACE FLAT 19 W / 27 W



Product benefits

- 3000 K and 4000 K LEDs integrated
- Indoor use with high luminous efficacy of up to 140 lm/W
- High color consistency with SDCM 3
- Tool-free electrical connection with plug connectors
- Very homogenous light with a slight backlight effect
- Prepared for SURFACE FLAT SENSOR integration
- 5 years guarantee

Product features

- Type of protection: IP20
- Polycarbonate (PC) housing, PC-diffusor
- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- Impact resistance: IK08
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- Indoor use only, not suitable for outdoor use




TECHNICAL DATA

Electrical data


Nominal wattage	16.0 W
Nominal voltage	30...40 V
Mains frequency	50...60 Hz
Nominal current	450 mA

Photometrical data


Luminous flux	2660 lm
Luminous efficacy	140 lm/W
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	3 sdc _m
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °




LISOEV 330SQ 19W 830 SF FLAT
2490lm



LISOEV 330SQ 19W 840 SF FLAT
2660lm




LISOEV 330SQ 19W 830 SF FLAT
2490lm



LISOEV 330SQ 19W 840 SF FLAT
2660lm

Dimensions & Weight

Length	330.00 mm
Width	330.00 mm
Height	53.00 mm
Product weight	1038.00 g



LISOEV 330SQ 19W 830 840 SF
FLAT

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Ambient temperature range	-20...+45 °C
Temperature range at storage	-40...+80 °C
Type of protection	IP20
Dimmable	No
Mounting type	Surface

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Lifespan L80/B10 at 25 °C	100000 h
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h

Certificates & Standards

Standards	CE
Replaceable light source (EPREL)	Not replaceable







Additional product data









Product remark	Available from September 2024
Added function	EVERLOOP / MULTI SELECT



EQUIPMENT / ACCESSORIES


– Connection wire for direct installation integrated

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	UI LISOEV SF FLAT
 Legal information	Legal Insert SF FLAT LISOEV
 Legal information	LISO Insert SF FLAT LISOEV
 Legal information	Informationstext 18 Abs 4 ElektroG
 Declarations of conformity	CE Declaration SF FLAT
 Declarations of conformity UKCA	UKCA Declaration SF FLAT

Photometric and lighting design files	Document name
 IES file (IES)	LISOEV 330SQ 19W 830 SF FLAT 2490lm
 IES file (IES)	LISOEV 330SQ 19W 840 SF FLAT 2660lm
 LDT file (Eulumdat)	LISOEV 330SQ 19W 830 SF FLAT 2490lm
 LDT file (Eulumdat)	LISOEV 330SQ 19W 840 SF FLAT 2660lm
 UGR file (UGR table)	LISOEV 330SQ 19W 830 SF FLAT 2490lm
 UGR file (UGR table)	LISOEV 330SQ 19W 840 SF FLAT 2660lm
 Light distribution curve type cone	LISOEV 330SQ 19W 830 SF FLAT 2490lm
 Light distribution curve type cone	LISOEV 330SQ 19W 840 SF FLAT 2660lm

Photometric and lighting design files	Document name
 Light distribution curve type polar	LISOEV 330SQ 19W 830 SF FLAT 2490lm
 Light distribution curve type polar	LISOEV 330SQ 19W 840 SF FLAT 2660lm

Tender texts	Document name
 Tender documents	SURFACE FLAT LIGHT SOURCES 330 SQ 19W 830 840 SF FLAT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854312250	Folding box 1	57 mm x 336 mm x 336 mm	1234.00 g	6.44 dm ³
4099854312267	Shipping box 6	355 mm x 353 mm x 358 mm	8065.00 g	44.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



SKU	DESCRIPTION	UNIT	SKU	DESCRIPTION	UNIT
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1
4099854312250	LISOEV 330SQ 19W 830 SF FLAT	1	4099854312250	OF FLAT 190 330 SF 19W 830	1

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.