

# PRODUCT DATASHEET Undercabinet Socket Flood 830 DIM Black Extension

UNDERCABINET SOCKET FRAMELESS | Frameless undercabinet luminaire kit with power sockets and USB-C ports



#### Areas of application

- Kitchens, Living areas, Shelf and undercabinet lighting

#### Product benefits

- Multifunctional Use: Lighting and Power / Charging Function in one Luminaire
- Two power sockets and two USB-C ports to support additional equipment (kitchen devices, mobile devices)
- Individual arrangement of the light modules to the right or left or mixed, depending on your own needs
- Connection of up to 4 light modules via simple click system

#### **Product features**

- The socket module can supply devices with an output of up to 2400W
- 2x EU sockets (max.10A) and 2x USB C (5V 2.4A)
- Switch on and off by pressing and holding the button 1 second
- Stepless dimming by pressing and holding the button more longer than 3 seconds
- Starter Kit includes one socket module and two light modules
- Extension kit includes one light module



- Lifetime up to 30,000 h

#### TECHNICAL DATA

### Electrical data


Nominal wattage	3.85 W
Nominal voltage	36 V
Mains frequency	5060 Hz
Nominal current	110.000 mA
Inrush current time T <sub>h50</sub>	38 µs
Protection class	III
Operating mode	Mains voltage

#### Photometrical data

Luminous flux	250 lm
Total luminous flux of contained light sources	300 lm
Luminous efficacy	50 lm/W
Color temperature	3000 K
Light color (designation)	Warm white
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	110°

## Dimensions & Weight

Length	179.00 mm
Width	81.00 mm
Height	21.00 mm
Product weight	140.00 g
Cable length	1500 mm



# UNDERCABINET SOCKET FL EXT 830 D BK line drawing

#### Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

#### **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Plug type F
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Cabinet undersides
Application environment	Indoor
Adjustable	Yes
With light source	Yes
Replaceable light source	No

#### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Certificates & Standards

Standards	CE
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

#### Safety advice

- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

#### DOWNLOAD DATA

Documents and certificates		Document name	
PDF	User instruction / safety instructions	Undercabinet Socket	
PDF	Legal information	TRACKLIGHT SPOT ZOOM D85	
Declarations of conformity		UNDERCABINET SOCKET FL KIT	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075842786	Folding box	27 mm x 92 mm x 238 mm	245.00 g	0.59 dm <sup>3</sup>
4058075842793	Shipping box 8	255 mm x 123 mm x 215 mm	2224.00 g	6.74 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.