


PRODUCT DATASHEET M 455 H 48 RB -BF-F9

PV PANELS HJT-TYPE BIFACIAL BLACK | HJT bifacial photovoltaic panels with black frame



Areas of application

- Commercial and industrial installations
- Residential installations



Product benefits

- HJT solar cells achieve the highest degree of efficiency due to heterojunction technology
- $\ \, \text{Glass-glass modules offer improved protection against moisture, mechanical loads and fire protection}$
- HJT technology significantly reduces the power degradation of the cells over the years
- 25-years of product guarantee, 30-years of linear power output guarantee
- Limited PID-effect (potential induced degradation) thanks to strict quality control in production process
- Durable design and highest production standards guarantees operational reliability and quality

Product features

- Heterojunction (HJT) solar modules with glass-glass protection
- Bifacial both sides of the panel are absorbing the light
- Original Stäubli MC4 EVO 2 connectors
- Available in a long cable version
- Frame made of anodized aluminum alloy
- Maximum static load up to 5400 Pa

TECHNICAL DATA

ELECTRICAL DATA STC

Maximum Power Pmax (STC)	455 W
Maximum Power Current Imp (STC)	14.77 A
Short Circuit Current Isc (STC)	15.47 A
Maximum Power Voltage Vmp (STC)	30.81 V
Open Circuit Voltage Voc (STC)	36.66 V
Module efficiency factor (STC)	22.77 %

ELECTRICAL DATA NMOT

Maximum Power Pmax (NMOT)	346 W
Maximum Power Current Imp (NMOT)	11.80 A
Short Circuit Current Isc (NMOT)	12.37 A
Maximum Power Voltage Vmp (NMOT)	29.32 V
Open Circuit Voltage Voc (NMOT)	34.99 V

ELECTRICAL DATA STC and NMOT

Power tolerance	3 %

MECHANICAL DATA

Type of Faciality	Bifacial	
Cell material	Mono crystalline	
Number of cells	96	
Number of bypass diodes	3	
With frame	Yes	
Type of connection	Staubli MC4 EVO2	
Width	1134 mm	
Length	1762 mm	
Height	30 mm	
Product weight	23000.000 g	
Cable length	1.2 m	
Glass with anti-reflection coating	Yes	
Colour cells	Dark blue	
Colour frame	Black	
Front Glass	2.0 mm coated semi-tempered glass	
Back Glass	1.6 mm tempered glass / Anti-reflective coating / Double glass	

TEMPERATURE RATINGS

Nominal operating cell temperature	44 °C
Temperature coefficient lsc	0.040 %/K

	2000
Temperature coefficient Pmpp	-0.290 %/K
Temperature coefficient Uoc	-0.240 %/K

OPERATING CONDITIONS

Maximum series fuse rating	30 A
Temperature range in operation	-40+85 °C
Front Side Maximum Static Loading	5400 Pa
Rear Side Maximum Static Loading	2400 Pa
Reverse current load	30 A

EQUIPMENT / ACCESSORIES

- Product is delivered as a whole, no assembly required from customer
- MC4 EVO 2 connectors are fitted to the panel
- 3 bypass diodes are already installed in the panel

DOWNLOAD DATA

Documents and certificates		Document name	
User instruction / safety instructions		PV MODULE	
Declarations of conformity CE declaration M455H48RB-BF-F9		CE declaration M455H48RB-BF-F9	
PDF	Product family datasheet	M440~460H48RB-BF-F9_EN	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854346194	Shipping box 36	1,784 mm x 1,140 mm x 1,140 mm	843000.00 g	2318.49 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.