

PRODUCT DATASHEET

NAV 70 LED FILAMENT P 6000LM 30.7W 740 E27

NAV LED FILAMENT P | LED replacement for NAV lamps in demanding outdoor applications

PERFOR-
MANCE
CLASS

Areas of application

- Streets
- Area lighting
- Pedestrian zones
- Parks
- Outdoor applications only in suitable luminaires

Product benefits

- Same design as traditional NAV lamps with clear, tubular full glass bulb
- Saves up to 62 % energy when used as replacement for sodium vapour lamps (NAV)
- Full use of reflector of existing luminaire thanks to 360 degree beam angle
- Better color rendering and enhanced visibility compared to traditional sodium vapor lamps (NAV)
- Very light weight product
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

Product features

- Suitable for operation with conventional control gear (CCG) for NAV or 230 V mains
- Very high efficiency of 185 lm/W
- Power factor: 0.9
- Type of protection: IP65
- High surge protection: up to 4 kV (L-N)
- Very wide ambient temperature range of -20...+60 °C



TECHNICAL DATA**Electrical data**

Nominal wattage	30.7 W
Construction wattage	30.70 W
Nominal voltage	220...240 V
Operating mode	CCG, AC Mains
Claimed equiv. conventional lamp power	70 W
Nominal current	150 mA
Type of current	AC
Inrush current	10.15 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	19
Max. lamp number on MCB B10 A - CCG without compensation	24
Max. lamp number on MCB B10 A - CCG with compensation	12
Max. lamp number on MCB B16 A	31
Max. lamp number on MCB B16 A - CCG without compensation	38
Max. lamp number on MCB B16 A - CCG with compensation	20
Total harmonic distortion	< 20 %
Power factor λ	> 0.90
Surge capability (L-N)	4 kV

Photometrical data

Luminous flux	6000 lm
Nominal useful luminous flux 90°	6000 lm
Luminous efficacy	195 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	70
Light color	740
Standard deviation of color matching	≤6 sdcn
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1



EPREL data spectral diagram PROF
LEDr 4000K

Light technical data

Beam angle	360 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	227.00 mm
Diameter	46.00 mm
Maximum diameter	46 mm
Product weight	150.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+60 °C ¹⁾
Maximum temperature at tc test point	102 °C

1) Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	60000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27
-----------------------------	-----

Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Available from September 2025

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	B ¹⁾
Energy consumption	31.00 kWh/1000h
Type of protection	IP65
Standards	CE / UKCA / EAC / ENEC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	NAV 70 LED FIL
-----------------	----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015









Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	227.00 mm
Height	46.00 mm
Width	46.00 mm
Chromaticity coordinate x	0.382


Chromaticity coordinate y	0,38
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	2295935
Model number	AC69396

Safety advice

- Not suitable for operation with ignitors.
- Operation on the capacitor can lead to a reduction of the power factor of the system.
- When installed horizontally, the t_c point of the lamp is located on the top side of the lamp.
- Use in tight luminaires and luminaires with tight reflectors not recommended.
- Only suitable for temperatures of up to 60 °C inside of the luminaire. Use in tight luminaires and luminaires with tight reflectors not recommended.
- All electrical connections must be made by a qualified person.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	FIL P lamp
	Declarations of conformity UKCA	FIL P lamp
Photometric and lighting design files		Document name
	IES file (IES)	NAV 70 LED FIL P 6000LM 30.7W 740 E27
	LDT file (Eulumdat)	NAV 70 LED FIL P 6000LM 30.7W 740 E27
	UGR file (UGR table)	NAV 70 LED FIL P 6000LM 30.7W 740 E27
	Light distribution curve type polar	NAV 70 LED FIL P 6000LM 30.7W 740 E27

Photometric and lighting design files		Document name
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854469794	Folding box 1	57 mm x 57 mm x 253 mm	195.00 g	0.82 dm ³
4099854469800	Shipping box 6	187 mm x 131 mm x 275 mm	1360.00 g	6.74 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.