

PRODUCT DATASHEET Lunetta Flare 830 Black

LUNETTA FLARE | Indoor mobile luminaires



Areas of application

- General indoor illumination
- Nightlight as an orientation light or safety light for children's rooms, stairs, or bedrooms

Product benefits

- Attractive and functional design

Product features

- Hidden Motion and a Day - Night sensor and dimming function for maximized energy savings

TECHNICAL DATA

Electrical data


Nominal wattage	0.20 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	16.000 mA
Inrush current	0.016 A
Inrush current time T _{h50}	580 µs
Max. number of luminaires per miniature circuit breaker B16	800
Max. number of luminaires per miniature circuit breaker C10	500
Max. number of luminaires per miniature circuit breaker C16	800
Power factor λ	≥ 0.01
Total harmonic distortion	< 50 %
Protection class	II .
Operating mode	Mains voltage

Photometrical data

Luminous flux	3 lm
Luminous efficacy	15 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG0
Beam angle	360 °

Dimensions & Weight

Length	36.50 mm
Width	73.80 mm
Height	104.40 mm
Product weight	52.00 g



Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	USB Type-C
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Socket
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Number of switching cycles	12500

Certificates & Standards

Standards	CE / EAC
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from June 2025

Safety advice

- This product is not a toy. It should not be left unattended in the hands of children or operated by children.
- Not designed as a replacement for conventional lighting in private household.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Legal information	Safety Insert LUNETTA	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854444418	Blister 1	80 mm x 140 mm x 195 mm	65.00 g	2.18 dm ³
4099854444425	Shipping box 6	495 mm x 154 mm x 212 mm	648.00 g	16.16 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.