

PRODUCT DATASHEET

Decor Yoyo Pendant 6.5W 830 Beige

Decor Yoyo Pendant | Decorative luminaires made of beige metal with integrated LED



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- Adjustable height
- Minimalistic style fits to every room
- Geometric shapes meet even illumination
- Easy mounting

Product features

- Housing material: metal and plastic
- High-power LED
- Color temperature: 3,000 K



TECHNICAL DATA**Electrical data**


Nominal wattage	6.50 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	45.000 mA
Inrush current	0.045 A
Inrush current time T_{h50}	3 μ s
Max. number of luminaires per miniature circuit breaker B16	284
Max. number of luminaires per miniature circuit breaker C10	177
Max. number of luminaires per miniature circuit breaker C16	284
Power factor λ	0.50
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	390 lm
Total luminous flux of contained light sources	800 lm
Luminous efficacy	60 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	< 6 sdcn
Photobiological safety group acc. to EN62778	RG0
Beam angle	110 °

Dimensions & Weight

Diameter	150.00 mm
Height	1890.00 mm
Product weight	530.00 g



DECOR YOYO PENDANT 6.5W 830
BG

Materials & Colors

Product color	Beige
Housing color	Beige
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Suspended
Mounting location	Ceiling
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
-----------	-----------

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from June 2025
----------------	--------------------------

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR YOYO PENDANT+LINEAR

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075846982	Folding box 1	202 mm x 202 mm x 147 mm	834.00 g	6.00 dm ³
4099854476167	Shipping box 4	430 mm x 215 mm x 325 mm	3796.00 g	30.05 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.