

PRODUCT DATASHEET

UB LTRN ASYM 6M V 29W ML 83040 GY

URBAN LANTERN ASYMMETRIC WITH CABLE | For pathway, bicycle path lighting applications with preassembled connection cable



VALUE
CLASS

Areas of application

- Replacement for luminaires with mercury vapor or metal halide lamps
- Public areas
- Parks
- Residential areas
- Pedestrian zones
- Streets

Product benefits

- Easy installation due to preassembled long cable
- Highly versatile due to selectable CCT and power steps (Power Select - PS)
- Low flicker light thanks to special electronic control gear
- Energy savings thanks to system efficacy of up to 139 lm/W
- Bright, robust and durable

Product features


- Long preassembled connection cable included
- Protection class: II
- Lifetime (L80/B10): up to 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK10
- Asymmetric light distribution

TECHNICAL DATA**Electrical data**


Nominal wattage	29 W / 25 W / 20 W / 15 W
Nominal voltage	220...250 V
Mains frequency	50...60 Hz
Nominal current	70mA / 90mA / 110mA / 130 mA
Inrush current	25.8 A
Inrush current time T_{h50}	330 μ s
Max. number of luminaires per miniature circuit breaker B16	8
Max. number of luminaires per miniature circuit breaker C10	8
Max. number of luminaires per miniature circuit breaker C16	13
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Surge capability (L-N)	6 kV
Operating mode	Integrated LED driver

Photometrical data


Luminous flux	3945 lm / 3400 lm / 2720 lm / 2040 lm
Luminous efficacy	136 lm/W
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	80
Standard deviation of color matching	5 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	< 1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	165° x 65 °




UB LTRN ASYM 6M V 29W ML 830
GY LEDV



UB LTRN ASYM 6M V 29W ML 840
GY LEDV



UB LTRN ASYM 6M V 29W ML 830
GY LEDV




UB LTRN ASYM 6M V 29W ML 840
GY LEDV

Adjustable attributes

upper attributes	Array / Array / Array / Array / Array / Array / Array / Array
------------------	---

Dimensions & Weight

Diameter	395.00 mm
Height	417.00 mm
Product weight	4562.00 g
Cable length	6000 mm



URBAN LANTERN

Materials & Colors

Product color	Gray
Housing color	Gray
RAL Color (most similar)	RAL 7024
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Temperature range at storage	-35...+80 °C
Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Post top
Mounting location	Pole
Application environment	Outdoor
Adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	56000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	765...650...520...390 mA
ECG - Output ripple current	< 20 %

Certificates & Standards

Standards	CE / UKCA / EAC / ENEC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

Product remark	Available from October 2025
Added function	MULTI SELECT

EQUIPMENT / ACCESSORIES

- Additional screws included for pole diameter of 42 mm

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	URBAN LANTERN G11245371
	Legal information	Safety Insert G11244388
	Legal information	Legal Insert G11245621
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	LSI Insert G11246562 Urban Lantern
	Declarations of conformity	URBAN LANTERN
	Declarations of conformity UKCA	URBAN LANTERN

	Photometric and lighting design files	Document name
	IES file (IES)	UB LTRN ASYM 6M V 29W ML 830 GY LEDV
	IES file (IES)	UB LTRN ASYM 6M V 29W ML 840 GY LEDV
	LDT file (Eulumdat)	UB LTRN ASYM 6M V 29W ML 830 GY LEDV

Photometric and lighting design files		Document name
	LDT file (Eulumdat)	UB LTRN ASYM 6M V 29W ML 840 GY LEDV
	Light distribution curve type cone	UB LTRN ASYM 6M V 29W ML 830 GY LEDV
	Light distribution curve type cone	UB LTRN ASYM 6M V 29W ML 840 GY LEDV
	Light distribution curve type polar	UB LTRN ASYM 6M V 29W ML 830 GY LEDV
	Light distribution curve type polar	UB LTRN ASYM 6M V 29W ML 840 GY LEDV
CAD/BIM files		Document name
	BIM Revit 3D	Urban Lantern
Tender texts		Document name
	Tender documents	URBAN LANTERN ASYMMETRIC WITH CABLE 6M V 29W ML 83040 GY-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854649868	Shipping box 1	435 mm x 435 mm x 220 mm	4927.00 g	41.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.