

# PRODUCT DATASHEET SMART+ ZIGBEE Dimmable Classic P40 4.9W E14

SMART+ ZIGBEE Classic Dimmable | Classic bulb shape with Zigbee technology



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

#### Product features

- Control via compatible smart home system (gateway and app)
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Network protocol: ZigBee 3.0
- Dimmable
- Lifetime: up to 20,000 h
- For full functionality connection to a compatible smart home System (gateway and app) required



4.9W E14




#### **TECHNICAL DATA**

#### Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	220240 V
Nominal current	38 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50
Claimed equiv. conventional lamp power	40 W
Operating mode	AC Mains

## Photometrical data

Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	95 lm/W
Adjustable color temperature	2700 K
Color temperature	2700 K
Color rendering index Ra	80
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4



Everlight 67-23ST KKE 2700K

## Light technical data

		Beam angle	200 °
--	--	------------	-------

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

# Dimensions & Weight



Product weight	23.00 g
Diameter	47.00 mm
Maximum diameter	47 mm
Length	92.00 mm
Width	47 mm
Height	47 mm
Outer bulb [PICOS]	P40

## Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of service lifetime	0.95

#### Colors & materials

Product color	White
Housing color	White

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C

## Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E14

# Capabilities

Dimmable	Yes 1)
Compatible smart home technology	Amazon Alexa / Google Home / Apple Home / Samsung SmartThings

<sup>1)</sup> Via App

## Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	5.00 kWh/1000h
Standards	CE
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	E14	
Connected light source (CLS)	Yes	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	
Correlated colour temperature type	SINGLE_VALUE	
Standby power	2 0.5 W	
Networked standby power for CLS	2 0.5 W	
Claim of equivalent power	Yes	
Chromaticity coordinate x	0.463	
Chromaticity coordinate y	0.42	
R9 Colour rendering index	1	
Beam angle correspondence	SPHERE_360	
Survival factor	0,9	
Displacement factor	0 W	
LED light source replaces a fluorescent light source	No	
EPREL ID	1160673	
Model number	AC41287,AC41287	

#### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions		
PDF	Declarations of conformity	SMART ZB DIM A60 / B40 / P40 / PAR16	
PDF	EU Data Act	SMART ZigBee Lamps and Luminaires	
	Photometric and lighting design files	Document name	
47	Spectral power distribution	Everlight 67-23ST KKE 2700K	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075729100	Folding box 1	56 mm x 78 mm x 82 mm	49.00 g	0.36 dm <sup>3</sup>
4058075729117	Shipping box 4	162 mm x 122 mm x 96 mm	268.00 g	1.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.