

PRODUCT DATASHEET P CLAS P 40 FR 5 W/2700 K E14

PARATHOM® CLASSIC P DIM | Dimmable LED lamps, classic mini-ball shape



Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

Product features

- Professional LED lamps for line voltage
- Dimmable
- Long lifetime up to 25,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	5 W
Construction wattage	5.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	29 mA
Type of current	AC
Inrush current	0.75 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	150
Max. lamp number on MCB B16 A	250
Power factor λ	> 0.80

Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	94 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	180 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	78.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm

0+40 °C 04 °C 00000 70 0.90		
04 °C 00000 70		
00000 70		
70		
70		
0.90		
4		
0 mg		
es		
osted		
All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / In preparation		
98		
<u>+</u> 1)		
00 kWh/1000h		
IP20		
G1		
EDPCLP40D 5W/8		
4		

Length	78.00 mm
Height	45.00 mm
Width	45.00 mm

DOWNLOAD DATA

	Photometric and lighting design files Document name	
	IES file (IES)	AC08399_CLP40D 5,3W 230VFR E14
LDT file (Eulumdat)		AC08399_CLP40D 5,3W 230VFR E14
	Light distribution curve type polar	LEDPCLP40D 5,3W 827 230VFR E14 FS1 OSRAM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075292352	Folding box 1	46 mm x 46 mm x 93 mm	46.00 g	0.20 dm ³
4058075292369	Shipping box 10	240 mm x 101 mm x 108 mm	518.00 g	2.62 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.