

PRODUCT DATASHEET

LED R80 100 36° DIM P 9.6W 827 E27

PARATHOM® DIM R80 | Dimmable LED reflector lamps R80 with retrofit screw base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Indoors and outdoors
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Stepless dimming
- Very high dimmer compatibility, see also www.ledvance.com/dim
- Instant 100 % light, no warm-up time

Product features

- LED alternative to high voltage halogen lamps
- High color consistency: ≤ 5 sdcn
- Dimmable
- Base: E27
- Lamp made of glass
- Very high color rendering CRI > 90



– Lifetime up to 25,000 h


TECHNICAL DATA

Electrical data

Nominal wattage	9.6 W
Construction wattage	9.60 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	100 W
Nominal current	46.3 mA
Type of current	AC
Inrush current	1.3 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	101
Max. lamp number on MCB B16 A	162
Power factor λ	0.70

Photometrical data

Luminous intensity	1300 cd
Luminous flux	670 lm
Nominal useful luminous flux 90°	670 lm
Luminous efficacy	69 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤5 sdcM
Rated peak intensity	1300 cd
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	0.2
Stroboscope effect metric (SVM)	0.4




Everlight 67-23ST KKE 2700K

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	113.00 mm
Diameter	80.00 mm
Maximum diameter	80 mm
Product weight	228.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	102 °C

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000

Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G 1)
Energy consumption	10.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG1

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations


Order reference	LEDPR80100D 9,6
-----------------	-----------------




Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE

Claim of equivalent power	Yes
Length	113.00 mm
Height	80.00 mm
Width	80.00 mm
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.400
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0,9
Displacement factor	0.70
LED light source replaces a fluorescent light source	No
EPREL ID	522939
Model number	AC32669

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	R39 R50 R63 R80 LED lamp

Photometric and lighting design files		Document name
	IES file (IES)	R80 100 dim 36 CRI80 2700 E27
	LDT file (Eulumdat)	R80 100 dim 36 CRI80 2700 E27
	Spectral power distribution	Everlight 67-23ST KKE 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075607972	Folding box 1	82 mm x 82 mm x 118 mm	246.00 g	0.79 dm ³
4058075607989	Shipping box 10	449 mm x 188 mm x 146 mm	2777.00 g	12.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
 - For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
 - For Guarantee see www.ledvance.com/guarantee
-

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.