

PRODUCT DATASHEET DULUX LED D13 EM & AC MAINS 6W 865 G24D-1

OSRAM DULUX LED D EM & AC MAINS | LED replacement for CFLni with 2-pin G24d base for CCG



Areas of application

- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants

Product benefits

- Easy installation
- Low energy consumption
- Easy relamping thanks to compact design
- Operation directly on 230 V AC mains possible

Product features

- LED replacement for conventional compact fluorescent lamps for use in CCG luminaires or on AC mains
- Rotatable base around its longitudinal axis (± 90°)
- Lifetime up to 30,000 h
- Single-ended two-pin plug-in G24d base
- Type of protection: IP20
- Mercury-free lamps





TECHNICAL DATA

Electrical data

Nominal wattage	6 W	
Construction wattage	6.00 W	
Nominal voltage	220240 V	
Operating mode	Conventional control gear (CCG), AC ¹⁾	
Claimed equiv. conventional lamp power	13 W	
Nominal current	29 mA	
Type of current	AC	
Inrush current	14.4 A	
Input voltage DC	186260 V	
Operating frequency	50/60 Hz	
Mains frequency	50/60 Hz	
Max. lamp number on MCB B10 A	41	
Max. lamp number on MCB B10 A - CCG without compensation	138	
Max. lamp number on MCB B10 A - CCG with compensation	10	
Max. lamp number on MCB B16 A	52	
Max. lamp number on MCB B16 A - CCG without compensation	221	
Max. lamp number on MCB B16 A - CCG with compensation	12	
Total harmonic distortion	≤ 20 %	
Power factor λ	> 0.90	

¹⁾ Check ECG compatibility at ledvance.com/compatibility

Photometrical data

Luminous flux	660 lm
Nominal useful luminous flux 90°	2250 lm
Luminous efficacy	110 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0

Stroboscope effect metric (SVM)	0.4
---------------------------------	-----



EPREL data spectral diagram PROF LEDr 6500K

Light technical data

Beam angle	120 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	138.00 mm
Diameter	35.00 mm
Tube diameter	27,0 mm
Maximum diameter	45 mm
Product weight	50.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹⁾
Maximum temperature at to test point	73 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000

Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	G24d-1
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	Available from June 2025
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	E 1)
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0
n	
Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo	owest efficiency)
Country-specific categorizations	
Order reference	DULUX LED D13 E
OGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G24d-1
Connected light source (CLS)	No
Color-tuneable light source	No
Envolono	No

No

No

No

Envelope

Anti-glare shield

High luminance light source

Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	No
Length	138.00 mm
Height	35.00 mm
Width	35.00 mm
Chromaticity coordinate x	0.3123
Chromaticity coordinate y	0.3282
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	2206895,2324435
Model number	AC71075,AC81495

Safety advice

- Not suitable for tandem operation.
- The operating temperature range of DULUX LED is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.
- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DULUX LED D EM
PDF	Extended installation guide	Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	LEDTUBE
PDF	Declarations of conformity UKCA	LEDTUBE

Photometric and lighting design	gn files	Document name	
IES file (IES)		DULUX LED D13 EM 6W 865 G24D-1 OSRAM	
LDT file (Eulumdat)		DULUX LED D13 EM 6W 865 G24D-1 OSRAM	
UGR file (UGR table)		DULUX LED D13 EM 6W 865 G24D-1 OSRAM	
Light distribution curve type cone		DULUX LED D13 EM 6W 865 G24D-1 OSRAM	
Light distribution curve type p	olar	DULUX LED D13 EM 6W 865 G24D-1 OSRAM	
Spectral power distribution		EPREL data spectral diagram PROF LEDr 6500K	
Tender texts	Document name		
Tender documents	OSRAM DULUX LE	ED D EM AC MAINS 6W 865 G24D 1-en	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854502415	Folding box 1	37 mm x 49 mm x 151 mm	63.00 g	0.27 dm ³
4099854502422	Shipping box 10	203 mm x 110 mm x 165 mm	729.00 g	3.68 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.