

## PRODUCT DATASHEET

### LED VALUE CLAS A 10 W/6500 K B22d

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### Product benefits

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### Product features

- Color rendering index  $R_a$ :  $\geq 80$
- Not dimmable
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

|                                        |             |
|----------------------------------------|-------------|
| Nominal wattage                        | 10 W        |
| Construction wattage                   | 10.00 W     |
| Nominal voltage                        | 220...240 V |
| Claimed equiv. conventional lamp power | 75 W        |
| Nominal current                        | 84 mA       |
| Type of current                        | AC          |
| Operating frequency                    | 50...60 Hz  |
| Mains frequency                        | 50...60 Hz  |
| Power factor $\lambda$                 | > 0.50      |

### Photometrical data

|                                         |               |
|-----------------------------------------|---------------|
| Luminous flux                           | 1055 lm       |
| Nominal useful luminous flux 90°        | 1055 lm       |
| Luminous efficacy                       | 105 lm/W      |
| Lumen main.fact.at end of nom.life time | 0.70          |
| Light color (designation)               | Cool Daylight |
| Color temperature                       | 6500 K        |
| Color rendering index Ra                | 80            |
| Light color                             | 865           |
| Standard deviation of color matching    | ≤6 sdcn       |

### Light technical data

|               |         |
|---------------|---------|
| Beam angle    | 200 °   |
| Starting time | < 0.5 s |

### Dimensions & Weight

|                  |           |
|------------------|-----------|
| Overall length   | 117.00 mm |
| Diameter         | 60.00 mm  |
| Maximum diameter | 60 mm     |
| Product weight   | 32.00 g   |

### Temperatures & operating conditions

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

### Lifespan

|                                              |        |
|----------------------------------------------|--------|
| Number of switching cycles                   | 100000 |
| Lumen maintenance at end of service lifetime | 0.70   |

#### Additional product data

|                             |                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base (standard designation) | B22d                                                                                                                                                                                                                                                                                                                                         |
| Mercury content             | 0.0 mg                                                                                                                                                                                                                                                                                                                                       |
| Mercury-free                | Yes                                                                                                                                                                                                                                                                                                                                          |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

#### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

#### Certificates & Standards

|                                              |                  |
|----------------------------------------------|------------------|
| Energy efficiency class                      | A+ <sup>1)</sup> |
| Energy consumption                           | 10.00 kWh/1000h  |
| Type of protection                           | IP20             |
| Photobiological safety group acc. to EN62778 | RG0              |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

#### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | LVCLA7510W/8652 |
|-----------------|-----------------|

#### Energy labelling regulation data acc EU 2019/2015

|                                                     |           |
|-----------------------------------------------------|-----------|
| Light source cap-type (or other electric interface) | B22d      |
| Length                                              | 117.00 mm |
| Height                                              | 60.00 mm  |
| Width                                               | 60.00 mm  |

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075412736 | Folding box<br>1             | 64 mm x 64 mm x 131 mm               | 76.00 g      | 0.54 dm <sup>3</sup> |
| 4058075412743 | Shipping box<br>10           | 332 mm x 138 mm x 147 mm             | 914.00 g     | 6.73 dm <sup>3</sup> |

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854256028 | Shipping box<br>10           | 332 mm x 138 mm x 147 mm             | 812.00 g     | 6.73 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.