

## PRODUCT DATASHEET

### LED VALUE CLAS P 4.9 W/2700 K B22d

LED VALUE CLASSIC P | LED lamps, classic mini-ball shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### Product benefits

- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### Product features

- Color rendering index  $R_a \geq 80$
- Not dimmable
- Mercury-free lamps



TECHNICAL DATA

Electrical data

|                        |             |
|------------------------|-------------|
| Nominal wattage        | 4.9 W       |
| Construction wattage   | 4.90 W      |
| Nominal voltage        | 220...240 V |
| Nominal current        | 39 mA       |
| Type of current        | AC          |
| Operating frequency    | 50/60 Hz    |
| Mains frequency        | 50/60 Hz    |
| Power factor $\lambda$ | > 0.50      |

Photometrical data

|                                      |                     |
|--------------------------------------|---------------------|
| Luminous flux                        | 470 lm              |
| Luminous efficacy                    | 95 lm/W             |
| Light color (designation)            | Warm White          |
| Color temperature                    | 2700 K              |
| Color rendering index Ra             | ≥80                 |
| Light color                          | 827                 |
| Standard deviation of color matching | ≤6 sdc <sub>m</sub> |

Light technical data

|               |         |
|---------------|---------|
| Beam angle    | 160 °   |
| Starting time | < 0.5 s |

Dimensions & Weight

|                |          |
|----------------|----------|
| Overall length | 82.00 mm |
| Diameter       | 45.00 mm |
| Product weight | 20.00 g  |

Temperatures & operating conditions

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Lifespan

|                            |        |
|----------------------------|--------|
| Number of switching cycles | 100000 |
|----------------------------|--------|

Additional product data

|                             |      |
|-----------------------------|------|
| Base (standard designation) | B22d |
|-----------------------------|------|

|                 |        |
|-----------------|--------|
| Mercury content | 0.0 mg |
|-----------------|--------|

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | LVCLP40 4,9W/82 |
|-----------------|-----------------|

### Energy labelling regulation data acc EU 2019/2015

|                                                     |          |
|-----------------------------------------------------|----------|
| Light source cap-type (or other electric interface) | B22d     |
| Length                                              | 82.00 mm |
| Height                                              | 45.00 mm |
| Width                                               | 45.00 mm |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075625396 | Folding box<br>1             | 45 mm x 45 mm x 84 mm                | 28.00 g      | 0.17 dm <sup>3</sup> |
| 4058075625402 | Shipping box<br>10           | 233 mm x 98 mm x 96 mm               | 341.00 g     | 2.19 dm <sup>3</sup> |
| 4099854084676 | Shipping box<br>10           | 246 mm x 106 mm x 107 mm             | 345.00 g     | 2.79 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.