

PRODUCT DATASHEET

VALUE PAR 16 80 36 ° 7 W/6500 K GU10

LED VALUE PAR16 | LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Hospitality
- Restaurants
- Residential interiors
- Museums, art galleries

Product benefits

- Attractive lamp appearance
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Clear cast shadows for brilliant accent light
- Uniform illumination thanks to TIR-reflector and fly eye single optic design
- Energy savings of up to 91 % (compared to halogen lamps)
- High color consistency thanks to narrow binning
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Lamp made of glass
- High color consistency: < 6 SDCM
- Input voltage: 220...240 V_{AC}
- Lifetime up to 15,000 h
- Not dimmable



- Mercury-free lamps

TECHNICAL DATA

Electrical data

Nominal wattage	7 W
Construction wattage	7.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	80 W
Nominal current	40 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	0.70

Photometrical data

Luminous intensity	1100 cd
Luminous flux	650 lm
Luminous efficacy	92 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤ 6 sdc _m
Rated peak intensity	1100 cd

Light technical data

Beam angle	36 °
Warm-up time (60 %)	≤ 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	52.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	39.8 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	G 1)
Type of protection	IP20
Standards	CB / EMC / RoHS

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	LVPAR168036 7W/
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	GU10
Length	52.00 mm
Height	50.00 mm
Width	50.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075587830	Folding box 1	49 mm x 49 mm x 62 mm	46.80 g	0.15 dm³
4058075587847	Shipping box 10	255 mm x 107 mm x 72 mm	495.00 g	1.96 dm³

4099854263330	Shipping box 10	255 mm x 107 mm x 72 mm	521.00 g	1.96 dm³
---------------	--------------------	-------------------------	----------	----------

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.