

PRODUCT DATASHEET LED TUBE T9 C 22 EM 11W 840 G10q

LED TUBE T9 EM | Circular LED tubes for electromagnetic control gear (CCG)



Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Corridors, stairways, parking garages
- Domestic applications
- Decorative applications

Product benefits

- Quick, simple and safe replacement without rewiring
- Energy savings of up to 50% (compared to T9 fluorescent lamp on CCG)
- Also suitable for operation at low temperatures

Product features

- LED alternative to classic T9 fluorescent lamps in CCG luminaires
- Uniform illumination
- Lifetime up to 30,000 h
- Mercury-free and RoHS compliant





TECHNICAL DATA


Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220240 V
Operating mode	Conventional control gear (CCG), AC Mains
Nominal current	51 mA
Type of current	AC
Inrush current	11 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	25
Max. lamp number on MCB B10 A - CCG without compensation	94
Max. lamp number on MCB B10 A - CCG with compensation	16
Max. lamp number on MCB B16 A	31
Max. lamp number on MCB B16 A - CCG without compensation	150
Max. lamp number on MCB B16 A - CCG with compensation	20
Total harmonic distortion	< 20 %
Power factor λ	> 0.90

Photometrical data

Luminous flux	1320 lm
Luminous efficacy	120 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4

December 13, 2025, 20:35:30 LED TUBE T9 C 22 EM 11W 840 G10q



EPREL data spectral diagram PROF LEDr 6500K

Light technical data

Beam angle	110°
Warm-up time (60 %)	0.00 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	212.00 mm
Diameter	212.00 mm
Product weight	158.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹⁾
Maximum temperature at tc test point	75 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.96
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	G10q
-----------------------------	------

December 13, 2025, 20:35:30 LED TUBE T9 C 22 EM 11W 840 G10q

Mercury content	0.0 mg	
Mercury-free	Yes	
Capabilities		
Dimmable	No	
Certificates & Standards		

Energy efficiency class	E 1)
Energy consumption	11.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LEDTUBE T9C EM

LOGISTICAL DATA

Temperature range at storage	-20+80 °C
------------------------------	-----------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G10q
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	Yes
Length	212.00 mm
Height	212.00 mm
Width	212.00 mm
Chromaticity coordinate x	0.3818
Chromaticity coordinate y	0.3797

December 13, 2025, 20:35:30 LED TUBE T9 C 22 EM 11W 840 G10q

R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1340157
Model number	AC45079,AC45079

Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.
- Not suitable for emergency lighting.
- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name		
PDF	User instruction / safety instructions	LEDTUBE T9 C OSRAM		
PDF	Legal information	Informationstext 18 Abs 4 ElektroG		
POF	Declarations of conformity	LEDTUBE T9C EM		
PDF	Declarations of conformity UKCA	UKCA declaration_LEDTUBE T9C EM		
	Photometric and lighting design files	Document name		
	Photometric and lighting design files IES file (IES)	Document name LEDTUBE T9C EM V 22 11W 840 G10Q		
		110 1 1 1 1		
	IES file (IES)	LEDTUBE T9C EM V 22 11W 840 G10Q		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854042621	Folding box	38 mm x 220 mm x 260 mm	242.00 g	2.17 dm ³
4099854042638	Shipping box 10	397 mm x 251 mm x 300 mm	2760.00 g	29.89 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/osram-led-tube

Legal advice

- When used to replace a T9 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.