

# PRODUCT DATASHEET LED TUBE T9 C 32 EM 18.3W 840 G10q

LED TUBE T9 EM | Circular LED tubes for electromagnetic control gear (CCG)



#### Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Corridors, stairways, parking garages
- Domestic applications
- Decorative applications

#### Product benefits

- Quick, simple and safe replacement without rewiring
- Energy savings of up to 50% (compared to T9 fluorescent lamp on CCG)
- Also suitable for operation at low temperatures

#### **Product features**

- LED alternative to classic T9 fluorescent lamps in CCG luminaires
- Uniform illumination
- Lifetime up to 30,000 h
- Mercury-free and RoHS compliant






# TECHNICAL DATA

# Electrical data

Nominal wattage	18.3 W
Construction wattage	18.30 W
Nominal voltage	220240 V
Operating mode	Conventional control gear (CCG), AC Mains
Nominal current	82 mA
Type of current	AC
Inrush current	12 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	22
Max. lamp number on MCB B10 A - CCG without compensation	65
Max. lamp number on MCB B10 A - CCG with compensation	14
Max. lamp number on MCB B16 A	26
Max. lamp number on MCB B16 A - CCG without compensation	105
Max. lamp number on MCB B16 A - CCG with compensation	18
Total harmonic distortion	< 20 %
Power factor $\lambda$	> 0.90

# Photometrical data

Luminous flux	2200 lm
Luminous efficacy	120 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



EPREL data spectral diagram PROF LEDr 6500K

# Light technical data

Beam angle	110°
Warm-up time (60 %)	0.00 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	300.00 mm
Diameter	300.00 mm
Product weight	216.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C <sup>1)</sup>
Maximum temperature at tc test point	75 °C

<sup>1)</sup> Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.96
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	G10q
-----------------------------	------

December 12, 2025, 08:52:27 LED TUBE T9 C 32 EM 18.3W 840 G10q

0.0 mg		
Yes		
Capabilities Capabilities		
No		
Certificates & Standards		
E 1)		
19.00 kWh/1000h		

IP20

RG0

CE / EAC / UKCA

-20...+80 °C

# Country-specific categorizations

Temperature range at storage

Photobiological safety group acc. to EN62778

Type of protection

Standards

Order reference	LEDTUBE T9C EM
LOGISTICAL DATA	

Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G10q
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	Yes
Length	300.00 mm
Height	300.00 mm
Width	300.00 mm
Chromaticity coordinate x	0.3818
Chromaticity coordinate y	0.3797

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1340160
Model number	AC45082,AC45082

# Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.
- Not suitable for emergency lighting.
- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	LEDTUBE T9 C OSRAM
POF	Legal information	Informationstext 18 Abs 4 ElektroG
POF	Declarations of conformity	LEDTUBE T9C EM
POF	Declarations of conformity UKCA	UKCA declaration_LEDTUBE T9C EM
	Photometric and lighting design files	Document name
	IES file (IES)	LEDTUBE T9C EM V 32 18.3W 840 G10Q
	LDT file (Eulumdat)	LEDTUBE T9C EM V 32 18.3W 840 G10Q LEDV
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 6500K
-		

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854042683	Folding box	38 mm x 308 mm x 348 mm	229.00 g	4.07 dm <sup>3</sup>
4099854042690	Shipping box 10	397 mm x 329 mm x 386 mm	2941.00 g	50.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For current information see www.ledvance.com/osram-led-tube

#### Legal advice

- When used to replace a T9 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.