

# PRODUCT DATASHEET HAL CL A 46 W 240 V B22D

HALOGEN CLASSIC A | Halogen lamps, classic bulb shape



### Areas of application

- General illumination
- Mood lighting
- Entrance lighting
- Restaurants, hotels and similar prestigious applications

### **Product benefits**

- Simple direct replacement for conventional incandescent lamps
- The same pleasant quality of light as that of an incandescent lamp
- Instant 100 % light, no warm-up time
- Contains no mercury
- UV filter

### **Product features**

- 100 % dimmable
- Perfect color rendering (Ra: 100)
- Average life: 2,000 h



# TECHNICAL DATA

### Electrical data

Nominal wattage	46 W
Construction wattage	46.00 W
Nominal voltage	240 V

# Photometrical data

Luminous flux	700 lm
Luminous efficacy	15 lm/W
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027

# Dimensions & Weight

Overall length	96.00 mm
Diameter	55.00 mm
Product weight	31.00 g

# Lifespan

Number of switching cycles	8000

# Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Bulb

# Capabilities

# Country-specific categorizations

Order reference	64543A FRCLA 46
-----------------	-----------------

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	93.00 mm

Height	55.00 mm
Width	55.00 mm

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854383816	Folding box 6	171 mm x 117 mm x 102 mm	263.00 g	2.04 dm <sup>3</sup>
4099854383823	Shipping box 96	487 mm x 359 mm x 224 mm	5052.00 g	39.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.