

# PRODUCT DATASHEET HALOPAR 120W E27 120W 220-240V E27

HALOPAR® 38 | Halogen lamps with parabolic reflector PAR38, with screw base



### Areas of application

- General illumination
- Object lighting
- Accent lighting

### Product benefits

- With whole glass reflector for brilliant lighting effects
- Instant 100 % light, no warm-up time
- Approved for use in open luminaires (to IEC 60598-1)
- Suitable for outdoor applications in approved luminaires
- Contains no mercury
- UV filter

### **Product features**

- Average life: 2,000 h
- 100 % dimmable
- Perfect color rendering (Ra: 100)
- Base: E27

### **TECHNICAL DATA**

### Electrical data

Nominal wattage	120 W
Construction wattage	120.00 W
Nominal voltage	220240 V

# Photometrical data

Luminous flux	1150 lm
Luminous efficacy	9.5 lm/W
Color temperature	2900 K
Color rendering index Ra	100
Light color	1029

# Dimensions & Weight

Overall length	134.00 mm
Diameter	123.0 mm
Product weight	337.00 g

# Lifespan

Number of switching cycles	8000
----------------------------	------

# Additional product data

Base (standard designation)	E27
Mercury-free	Yes

# Capabilities

# Country-specific categorizations

Order reference	64839 FL 120W 2
-----------------	-----------------

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	134.00 mm
Height	123.0 mm
Width	123.0 mm

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854145612	Folding box	111 mm x 111 mm x 139 mm	385.00 g	1.71 dm <sup>3</sup>
4099854145629	Shipping box	571 mm x 236 mm x 157 mm	4415.00 g	21.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.