

## PRODUCT DATASHEET

### HALOLINE PRO 120 W 240 V R7S

HALOLINE® PRO | Double ended halogen lamps with tube base



#### Areas of application

- General illumination
- Entrance lighting
- Pathway lighting
- Outdoor applications only in suitable luminaires
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Ideal for emphasizing and accentuating the structure of a room

#### Product benefits

- Brilliant accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO<sub>2</sub> emissions compared to standard version
- Lower thermal output (compared with the standard reference product)
- No transformer required
- Contains no mercury

#### Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index R<sub>a</sub>: 100



TECHNICAL DATA

Electrical data

Nominal wattage	120 W
Construction wattage	120.00 W
Nominal voltage	240 V
Nominal current	500 mA

Photometrical data

Luminous flux	2245 lm
Luminous efficacy	18 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
UV protection	No



349635\_HAL\_ohne\_UVS

Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight

Overall length	118.00 mm
Diameter	12.00 mm
Product weight	7.2 g

Lifespan

Lifespan L70/B50 at 25 °C	2000 h
---------------------------	--------

Additional product data

Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required / Technical and light values are subject to be changed

### Capabilities

Dimmable	Yes
Burning position	Any

### Certificates & Standards

Energy efficiency class	G
Energy consumption	120.00 kWh/1000h

### Country-specific categorizations

ILCOS	HDG-120-240-R7s-114,2
Order reference	64696 ECO

### Energy labelling regulation data acc EU 2019/2015


Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Standby power	0 W
Networked standby power for CLS	not applicable
Claim of equivalent power	No
Length	118.00 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0,437
Chromaticity coordinate y	0,404

Beam angle correspondence	SPHERE_360
Displacement factor	1
EPREL ID	714435,1554001
Model number	AC35332,AC51811

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

### DOWNLOAD DATA

Photometric and lighting design files		Document name
	Spectral power distribution	349635_HAL_ohne_UVS

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321977717	Folding box 1	20 mm x 21 mm x 136 mm	11.20 g	0.06 dm <sup>3</sup>
4008321977724	Shipping box 20	142 mm x 111 mm x 90 mm	272.00 g	1.42 dm <sup>3</sup>
4052899401310	Shipping box 720			
4099854147678	Shipping box 720	440 mm x 347 mm x 385 mm	10342.00 g	58.78 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.