

PRODUCT DATASHEET

DEL HO HPF 65 W/865 E40

OSRAM DULUX® EL HO HPF | CFL with integrated power supply



Areas of application

- General illumination
- High-quality domestic and professional environments
- Outdoor use in enclosed and ventilated luminaires only

Product features

- Available in 2 light colors: 827 and 865
- Average life: 10,000 h
- Good quality of light; color rendering index $R_a \geq 80$; constant chromaticity



TECHNICAL DATA

Electrical data

Nominal wattage	65 W
Construction wattage	65.00 W
Nominal voltage	230 V
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz

Photometrical data

Luminous flux	4000 lm
Luminous efficacy	62 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80...89
Light color	865

Dimensions & Weight

Overall length	257.00 mm
Diameter	90,0 mm
Product weight	301.00 g

Additional product data

Base (standard designation)	E40
Mercury content	5.0 mg
Mercury-free	No

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

Order reference	DULUX EL 65W/86
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E40
Length	254.00 mm
Height	90,0 mm
Width	90,0 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321339942	Folding box 1	114 mm x 114 mm x 291 mm	482.00 g	3.78 dm ³
4008321339959	Shipping box 6	356 mm x 240 mm x 302 mm	3209.00 g	25.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.