

PRODUCT DATASHEET

L 22 W/530 C G10Q

Basic T9 C | Circular fluorescent lamps 29 mm, with G10Q base



TECHNICAL DATA

Electrical data

Nominal wattage	22 W
Construction wattage	22.00 W
Nominal voltage	62 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	1150 lm
Luminous efficacy	52 lm/W
Color temperature	3000 K
Light color	30
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	215.90 mm
Diameter	29.00 mm
Product weight	127.00 g

Lifespan

Service life	5000 h
--------------	--------

Additional product data

Base (standard designation)	G10q
Mercury content	8.0 mg
Design / version	BASIC version
Product remark	These types are likely to be banned in the member states of the EU from April 2010

Country-specific categorizations

ILCOS	FSC-22/530-E-G10q-29/216
Order reference	L 22W/530 C G10

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
Length	216.00 mm
Height	29.00 mm

Width	29.00 mm
-------	----------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321841278	Sleeve 1	225 mm x 212 mm x 38 mm	196.00 g	1.81 dm³
4008321841285	Shipping box 12	450 mm x 238 mm x 227 mm	2747.00 g	24.31 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.