

PRODUCT DATASHEET

L 40 W/530 G10Q

Basic T9 C | Circular fluorescent lamps 29 mm, with G10Q base



TECHNICAL DATA

Electrical data

Nominal wattage	40 W
Construction wattage	40.00 W
Nominal voltage	115 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	2600 lm
Luminous efficacy	65 lm/W
Color temperature	3000 K
Color rendering index Ra	≥50
Light color	530
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	406.00 mm
Diameter	406 mm
Tube diameter	29 mm
Product weight	261.00 g

Lifespan

Service life	6000 h
--------------	--------

Additional product data

Base (standard designation)	G10q
Mercury content	7.2 mg
Design / version	BASIC version
Product remark	These types are likely to be banned in the member states of the EU from April 2010

Country-specific categorizations

ILCOS	FSC-40/530-E-G10q-29/406
Order reference	L 40W/530 C G10

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
---	------

Length	406.00 mm
Height	406 mm
Width	406 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321646064	Sleeve 1	421 mm x 411 mm x 38 mm	451.00 g	6.58 dm ³
4008321646071	Shipping box 12	452 mm x 436 mm x 431 mm	5865.00 g	84.94 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.