

# PRODUCT DATASHEET Element LD 30/220...240/700

ELEMENT LD | Constant Current - Indoor - on/off



### Areas of application

- Spotlight and downlight installations for shops
- Recessed luminaires
- Suitable for luminaires of protection classes I and II
- Suitable for indoor SELV installations

### **Product benefits**

- Compatible with LEDs with Chip-On-Board technology and discrete LEDs
- High efficiency
- Simple installation and wiring

### **Product features**

- Available with wattages up to 60 W
- Constant output current
- Integrated cable clamp for luminaire and independent installation
- Operated with Safety extra-low voltage (SELV): < 60 V
- Reversible overtemperature, overload, short-circuit and open-circuit protection


# **TECHNICAL DATA**

# Electrical data

Nominal wattage	8.00 W
Nominal output power	30 W
Nominal voltage	220240 V
Nominal output voltage	2142 V <sup>1)</sup>
Input voltage AC	220240 V <sup>2)</sup>
U-OUT (working voltage)	60 V
Nominal output current	700 mA
Inrush current	16 A
Output current tolerance	±10 %
Output ripple current (100 Hz)	40 % <sup>3)</sup>
Mains frequency	50/60 Hz
Total harmonic distortion	< 20 %
Power factor $\lambda$	0.98 4)
ECG efficiency	> 90 % <sup>5)</sup>
Device power loss	4.4 W <sup>6)</sup>
Max. ECG no. on circuit breaker 10 A (B)	25
Max. ECG no. on circuit breaker 16 A (B)	40
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	1 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV

<sup>1)</sup> DC voltage

# Dimensions & Weight



<sup>2)</sup>  $V_{AC}$ 

<sup>3)</sup> Ripple average at 100 Hz %

<sup>4)</sup> Full load at 230 V/50 Hz

<sup>5)</sup> At full load and 230 V / Typical / At 50 Hz

<sup>6)</sup> At 230 V / Input power 34.5 W max.

Length	103.00 mm
Mounting hole spacing, length	94,0 mm
Width	67.00 mm
Height	29.50 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup>
Cable cross-section, output side	0.51.5 mm <sup>2</sup>
Wire preparation length, input side	8.09.0 mm
Wire preparation length, output side	8.09.0 mm
Product weight	150.00 g

# Colors & materials

Casing material	Plastic
Body material	Plastic

# Temperatures & operating conditions

Ambient temperature range	-10+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

# Lifespan

ECG lifetime	30000 h <sup>1)</sup>
--------------	-----------------------

<sup>1)</sup> At  $T_{case} = 75$ °C at  $T_{c}$  point / 10% failure rate

# Additional product data

# Capabilities

Dimmable No	
Overheating protection	Automatic switch off, reversible by manual mains reset
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	1/11
Type of connection, output side	Push terminal

# Certificates & Standards

Approval marks – approval	CCC / CE / ENEC 10 / RCM
Standards	Acc. to IEC 61347-1 / Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 61547
Protection class	П
Type of protection	IP20

# LOGISTICAL DATA

Temperature range at storage	-1075 °C
------------------------------	----------

### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	Declarations of conformity	612430_ELEMENT CE declaration	
PDF	Declarations of conformity	Declaration of Conformity ELEMENT LD	
PDF	Certificates	730563_VDE Certificate	
PDF	Certificates	VDE ENEC Certificate 40038447	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899947108	Unpacked 1		150.00 g	
4052899947177	Shipping box 20	346 mm x 216 mm x 80 mm	3315.00 g	5.98 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.