

# PRODUCT DATASHEET OTi DALI 25/220...240/700 LT2

OPTOTRONIC® Intelligent - DALI LT2 | Compact constant current LED drivers



#### Areas of application

- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for use in luminaires with flexible current setting (DALI, CLO, LEDset)
- Suitable for indoor SELV installations
- Suitable for luminaires of protection classes I and II
- Suitable for downlights, spotlights and LED panels
- Installation via Cable Clamp Kit possible (depending on version of product)

#### **Product benefits**

- Versatile DALI window driver due to flexible output characteristic
- Very high efficiency
- Protection of the system thanks to thermal management and Smart Control
- High-quality dimming of 1...100 % by amplitude dimming

#### Versatile scope of application due to OSRAM DALI Technology:

- Easy to use in corridors and restrooms because of three-level Corridor function
- Touch DIM application: easy to control via pushbutton or sensor
- Energy efficient Touch DIM operation due to automatic switch-off at sufficient residual light
- Suitable for emergency Installations (acc. to EN 60598-2-22 and IEC 61347-2-13, appendix J) thanks to DC detection (0 Hz, pulsating DC), on/off switchable
- Feedback of power consumption and operating hours (Fit for SMART GRID)
- Suitable for buildings according to EPBD/BREEAM/LEED due to automatic Constant Lumen Output setting

#### Product features

- Supply voltage: 220...240 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Line voltage: 198...264 V
- Safety according to EN 61347-1, 61347-2-3, 61347-2-13, 62384
- RI suppression: to EN 55015/CISPR 15
- Line harmonics according to EN 61000-3-2

- Immunity according to EN 61547
- Lifetime: up to 100,000 h
- Type of protection: IP20
- Independent connection via through-looping (except OTi DALI 15)

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	27.00 W
Nominal output power	27 W <sup>1)</sup>
Nominal voltage	220240 V
Nominal output voltage	1254 V <sup>2)</sup>
Input voltage AC	198264 V <sup>3)</sup>
Input voltage DC	176276 V
U-OUT (working voltage)	60 V
Nominal current	0.14 A
Nominal output current	180700 mA <sup>4)</sup>
Inrush current	20 A <sup>5)</sup>
Output current tolerance	±3 %
Output ripple current (100 Hz)	< 1 % <sup>6)</sup>
Mains frequency	0/50/60 Hz
Total harmonic distortion	< 20 % <sup>7)</sup>
Power factor $\lambda$	> 0.95
ECG efficiency	88 % 8)
Device power loss	4,5 W
Max. ECG no. on circuit breaker 10 A (B)	50
Max. ECG no. on circuit breaker 16 A (B)	80
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Power loss in stand-by mode	< 0.1 W
Flickering metric (Pst LM)	≤1

<sup>1)</sup> Partial load 7...27 W

## Photometrical data

Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

<sup>2)</sup> Maximum 60 V

<sup>3)</sup> Permitted voltage range

<sup>4)</sup>  $_{\pm 3\%}$ 


<sup>5)</sup>  $t_{width}$  = 100 µs (measured at 50 %  $b_{eak}$ )

<sup>6)</sup> Ripple average at 100 Hz %

<sup>7)</sup> At full load, 220...240 V, 50 Hz / see graphs

<sup>8)</sup> Typical / At full load and 230 V

# Dimensions & Weight



Length	103.00 mm
Mounting hole spacing, length	94,0 mm
Width	67.00 mm
Height	29.50 mm
Cable cross-section, input side	0.21.5 mm <sup>2</sup> 1)
Cable cross-section, output side	0.21.5 mm <sup>2</sup> 1)
Wire preparation length, input side	8.09.0 mm
Wire preparation length, output side	8.09.0 mm
Product weight	149.00 g

<sup>1)</sup> Solid or flexible leads

## Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

# Temperatures & operating conditions

Ambient temperature range	-20+50 °C
Maximum temperature at tc test point	75 °C <sup>1)</sup>
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % <sup>2)</sup>

<sup>1)</sup> Maximum at the Tc-point

## Lifespan

ECG lifetime	50000 h / 100000 h <sup>1)</sup>
--------------	----------------------------------

<sup>1)</sup>  $T_{\text{C}}$  = 75°C, 0.2% / 1,000 h failure rate /  $T_{\text{C}}$  = 65°C, 0.1% / 1,000 h failure rate

# Additional product data

<sup>2)</sup> Maximum 56 days/year at 85 %

Encapsulated	No
Capabilities	
Dimmable	Yes
Dimming interface	DALI / Touch DIM / Touch DIM Sensor
Dimming range	1100 % <sup>1)</sup>
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	1/11
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

<sup>1)</sup> For maximum nominal output current

## Certificates & Standards

Approval marks – approval	ENEC 10 / VDE / EMC / EL / CE / DALI-2 / BIS
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384 / Acc. to EN 62386 / Acc. to IEC 62386-101:Ed2 / Acc. to IEC 62386-102:Ed2 / Acc. to IEC 62386-207:Ed1
Protection class	П
Type of protection	IP20

# LOGISTICAL DATA

Ì	Temperature range at storage	-2585 °C

# Energy labelling regulation data acc EU 2019/2015

Networked standby power for CLS	≤0.15 W
---------------------------------	---------

# DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	OPTOTRONIC LED Power Supply
POF	Addon technical information	729816_PPT OTi DALI Compact
PDF	Declarations of conformity	EATON(CEAG)-Conformity declaration AB42877_OTi_DALI_25_220-240_700_LT2

Documents and certificates	Document name
Declarations of conformity	EU Declaration of Conformity 3365628
Declarations of conformity	INOTEC- Conformity declaration AB42877_OTi_DALI_25_220-240_700_LT2
Certificates	VDE EMC Certificate 40038827
Certificates	VDE ENEC Certificate 40038447
EU Data Act	Connected Products and Related Software and Services
CAD/BIM files	Document name
CAD data 3D PDF	491387_OTi DALI 25 35 LT2 CADPDF 61119
	Declarations of conformity  Declarations of conformity  Certificates  Certificates  EU Data Act  CAD/BIM files

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899488144	Unpacked 1		149.00 g	
4052899488151	Shipping box 20	357 mm x 222 mm x 96 mm	3231.00 g	7.61 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.